

Part Number: 1201080286

Product Description: Micro-Change (M12) to Standard RJ-45 Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 8.0m (26.25') Length, 6.70mm (.264") Diameter,

Green

Status: Active

Engineering Number: E16A06011M080

Series Number: 120108

Product Category: Circular Industrial

Cordsets

Documents & Resources

Drawings

Drawing 1201080286_sd.pdf

Product Environment Compliance

Compliance

| China RoHS | Not Reviewed |
|--------------------|--------------|
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------------|---|
| Category | Circular Industrial Cordsets |
| Series | 120108 |
| Description | Micro-Change (M12) to Standard RJ- 45 Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male (Straight), 22 AWG, Shielded PUR Cable, 8.0m (26.25') Length, 6.70mm (.264") Diameter, Green |
| IP Rating | IP67 (M12 only) |
| Performance Category | 5e |
| Product Family | Brad Industrial Ethernet Solutions |
| Product Name | Industrial Ethernet,Micro-Change (M12) |
| Protocol | N/A |
| Туре | Double Ended |
| UPC | 78172538005 |

Agency

Electrical

| Current - Maximum per Contact | 1.5A |
|-------------------------------|------|
| Voltage - Maximum | 30V |

Physical

| Cable Diameter | 6.70mm (.264") |
|-------------------------|--------------------|
| Cable Length | 8.0m (26.25') |
| Color - Cable Jacket | Green |
| Connector End A | Micro-Change (M12) |
| Connector End B | RJ-45 (standard) |
| Coupling Style | Threaded |
| Gender | Male-Male |
| Keyway | D-Coded |
| LED Indicator | No |
| Material - Cable Jacket | PUR |

| Material - Connector Body | PUR, Thermoplastic |
|-------------------------------|----------------------|
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |
| Orientation | Straight to Straight |
| Poles | 4 |
| Temperature Range - Operating | -20° to +60°C |
| Wire/Cable Type | Shielded PUR |
| Wire Size (AWG) | 22 |

This document was generated on Sep 17, 2024