



**SPECIFICATIONS:**

Current Rating: 1A AC,DC  
 Voltage Rating: 150V AC,DC  
 Temperature Range: -40°C ~ +105°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66,UL94V-0(White)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	1.25	3.75	9P	10.00	12.50
3P	2.50	5.00	10P	11.25	13.75
4P	3.75	6.25	11P	12.50	15.00
5P	5.00	7.50	12P	13.75	16.25
6P	6.25	8.75	13P	15.00	17.50
7P	7.50	10.00	14P	16.25	18.75
8P	8.75	11.25	15P	17.50	20.00



CHANGJIANG CONNECTORS CO.,LTD.

Unit mm	Scale 8:1	Sheet 1 of 1
Draw BY: LIZQ	Approved : GONGYB	

Title :  
**1.25mm PITCH  
 HOUSING  
 ULTRA LOW PROFILE**

REV	DESCRIPTION	DATE	General Tolerance	ANGLE±
A0	NEW RELEESE	2009.05.10	x.xs≤0.25 x.xx≤0.20 x.xxx≤0.15	

DRAW NO : **A1257H-XP**      REV A0