



Deutsche Version

[Home](#)

[About Us](#)

Products

[Audio](#)

[Video](#)

Lighting

[Data Connectors](#)

[Industrial](#)

[Support](#)

[News](#)

[Sitemap](#)

Search

PRODUCTS ONLY

Search

© Neutrik® AG
All rights reserved
[Legal Notices](#)



Lighting

DMX Adapters

[back](#)

NA3F5M

Product

Connector Type Adapter

Electrical

Contact resistance $\leq 3 \text{ m}\Omega$

Dielectric strength 1,5 kVdc

Insulation resistance $> 2 \text{ G}\Omega$

Rated current per contact 7,5 A

Mechanical

Insertion force $< 20 \text{ N}$

Withdrawal force $< 20 \text{ N}$

Lifetime > 1000 mating cycles

Locking device Latch lock

Material

Contact plating $2 \mu\text{m Ag}$

Contacts Brass (CuZn39Pb3) (male)

Contacts Bronze (CuSn6) (female)

Insert Polyamide (PA 6.6 30 % GR)

Shell Zinc diecast (ZnAl4Cu1)

Shell plating Nickel

Environmental

Temperature range $-30 \text{ }^\circ\text{C}$ to $+80 \text{ }^\circ\text{C}$