

- Quick Links**
- RoHS/LF P/N Search
- Documentation**
- Customer drawing search
- Free search
- Services**
- Distributor list

Start > Search=211PC249S0033* > 211PC249S0033


211PC249S0033

211PC249S0033 : 24 Way coupling Female housing



Customer drawing

ACTIVE



[Add to Favorites](#)

FCI Brings You More

-
-

Specifications

[Download document](#)

[Mating Half](#)

General Mechanical Physical Terminal 1 Type Terminal 2 Type Environmental Other Features

General

Application	Chassis Control Confort Wire to Wire Component-to-Wire
Ways	24
Coding version	Black
Product Type	Housing
Coding	Yes
Features	Mechanical polarization Circumferential interface seal Terminal position assurance (T.P.A.) Pre-assembled front grids support blade terminal guiding and mating Acceptable wire size range from 0.35 to 4 mm ² Sealing protection IP 68 Easy locking cam with 2 positions possible High density 3 row connector system
Hybrid	Yes
Main Terminal family	SICMA
Main Terminal size	1.5 mm
Sealed	Yes
Terminal Size	18x1.5+6x2.8
Mechanical	
Connector mating force	< 70N
Physical	
Color	Black
Material	PBT
Temperature (Range)	-40°C to +125°C
Terminal 1 Type	
Terminal type 1	Sicma Female 1.5 mm Terminal
Ways for Terminal Type 1	18
Contact insertion force for Terminal Type 1	< 12N
Retention force (Contact) for Terminal Type 1	> 65N
Terminal 2 Type	
Terminal type 2	Sicma Female 2.8 mm Terminal
Ways for Terminal Type 2	6
Contact insertion force for Terminal Type 2	< 15N
Retention force (Contact) for Terminal Type 2	> 80N
Environmental	
IMDS	Yes
Other Features	
Market	Passenger Vehicles
Type	Female
Part Situation	Active
Disclaimer	For more information, please contact your local sales office. Displayed data is for information purposes only The supply of some products might be limited to some customers