

 $B_{\pm 0.25}$ 

A1257WV-S-XP - *** - *** - ***
1 2 3 4

(Blank): Nylon 9T,UL94V-0

GWT: Nylon 9T, UL94V-0, IEC 60335-1, 5th Edition
Glow Wire Capable.

(Blank): Ivory

BK: Black

$\overline{\text{OR}}$: Orange


TR: Tomato red

MG: Moss green

4.Finish:

(Blank): Tin over Nickel (Sn:≥80μin,Ni :≥30μin)

G: Gold over Nickel



Current Rating: 1A AC,DC
Voltage Rating: 50V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 30mΩ Max.
Insulation Resistance: 100MΩ Min.
Withstanding Voltage: 100V AC/minute
Pin Material: Phosphor Bronze
Material: Nylon 9T,UL94V-0

Part NO.	Dimensions(mm)	
	A	B
A1257WV-S-2P	1.25	5.75
A1257WV-S-3P	2.50	7.00
A1257WV-S-4P	3.75	8.25
A1257WV-S-5P	5.00	9.50
A1257WV-S-6P	6.25	10.75
A1257WV-S-7P	7.50	12.00
A1257WV-S-8P	8.75	13.25
A1257WV-S-9P	10.00	14.50
A1257WV-S-10P	11.25	15.75
A1257WV-S-11P	12.50	17.00
A1257WV-S-12P	13.75	18.25
A1257WV-S-13P	15.00	19.50
A1257WV-S-14P	16.25	20.75
A1257WV-S-15P	17.50	22.00

CJT con

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE 1.25mm PITCH 180° WAFER - SMD TYPE	
mm	6:1	1 of 1		
DRWN	CHK'D	APPR		
Dengchun Yi	Djankui Wan	Jack Yin		
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO. A1257WV-S-XP	REV A2
x.xx±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°				
				