

5380635-5 ✓ ACTIVE

TE Internal #: 5380635-5

Socket Length 6.45 mm [.254 in], PCB Hole Diameter 2.26 mm [.089 in], Open Bottom, .162 – .653 mm² Wire Size, 25 – 19 AWG Wire Size, Pin Sockets

[View on TE.com >](#)



Connectors > Socket Connectors > Pin Sockets > Miniature Spring Sockets: Open Bottom, Beryllium Copper, 7.5A



Socket Length: 6.45 mm [.254 in]

PCB Hole Diameter: 2.26 mm [.089 in]

Socket Sleeve Style: Open Bottom

Wire Size: .162 – .653 mm²

[All Miniature Spring Sockets: Open Bottom, Beryllium Copper, 7.5A \(9\)](#)

Features

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
Socket Sleeve Style	Open Bottom
Connector System	Cable-to-Board
Sealable	No

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Body Features

Sleeve Material	Copper
Sleeve Plating Material	Tin

Contact Features

Contact Spring Plating Material	Tin
Contact Spring Plating Thickness	2.03 μm[30 μin]
Contact Mating Area Plating Material Thickness	2.54 μm
Contact Base Material	Beryllium Copper



Contact Current Rating (Max)	7.5 A
------------------------------	-------

Termination Features

Insertion Method	Hand/Semi-Automatic
Termination Method to PCB	Through Hole - Press-Fit
Termination Method to Wire & Cable	Solder

Dimensions

PCB Thickness (Recommended)	.79 – 3.18 mm [.031 – .125 in]
Socket Length	6.45 mm [.254 in]
PCB Hole Diameter	2.26 mm [.089 in]
Wire Size	.162 – .653 mm ²
Mating Pin Diameter Range	.46 – 1.02 mm [.018 – .04 in]

Usage Conditions

Operating Temperature Range	-65 – 126 °C [-85 – 258 °F]
-----------------------------	-----------------------------

Operation/Application

Solder Process Feature	None
Circuit Application	Power & Signal

Packaging Features

Packaging Quantity	2000
Packaging Method	Bag, Loose Piece

Other

Spring Material	Beryllium Copper
-----------------	------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Solder Process Capability

Pin-in-Paste capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-377-MSSOB75
Miniature Spring Sockets: Open Bottom, Beryllium Copper, 7.5A

Customers Also Bought

TE Part #EC0020-000
05801202

TE Part #5050863-5
SOCKET,MIN-SPR SN-AU SER-2

TE Part #3-5338556-1
8/8 MOD JACK ASSY SE

TE Part #9-1625868-4
RP 2A 0.25W 49R9 0.1% 25PPM 1K RL

TE Part #6-2176388-4
RQ 1206 45R3 0.1% 10PPM 5K RL

TE Part #776164-4
35POS,AMPSEAL, SOC HSG ASSY,SLD, COD 4

TE Part #770854-3
CONTACT,AMPSEAL AU L/P

TE Part #6641710001
TMS-SCE Military Grade Sleeves



Documents

Product Drawings

[REUSABLE COMP RCPT TN SPR8CUP](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_5380635-5_O.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5380635-5_O.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5380635-5_O.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

[Reusable Receptacles For Component Testing](#)

English