



LV HRC fuse base Sz. 00, 1-pole 160 A 690 V (1000 V) with flat terminal for snapping onto standard mounting rail

Model			
product brand name	SENTRON		
product designation	LV HRC fuse system		
design of the thread of the nut	M8		
design of the thread of the connection screw	M8		
design of the product	LV HRC fuse base		
General technical data			
number of poles	1		
size of fuse system according to EN 60269-1	NH00		
utilization category	Without		
Supply voltage			
supply voltage			
• at AC	690 V		
• at DC	440 V		
Product details			
product component swivel-in mechanism	No		
maximum short-circuit current breaking capacity (I <sub>cu</sub> )			
• at AC rated value	120 kA		
• at DC rated value	25 kA		
Connections			
connectable conductor cross-section on terminal strip			
• minimum	1.5 mm <sup>2</sup>		
• maximum	16 mm <sup>2</sup>		
connectable conductor cross-section on plug-type connection			
• minimum	2.5 mm <sup>2</sup>		
• maximum	50 mm <sup>2</sup>		
tightening torque with screw-type terminals maximum	14 N·m		
type of electrical connection	With flat-type terminal		
• for main current circuit	flat connector		
Mechanical Design			
height	121 mm		
width	39 mm		
depth	61 mm		
fastening method	Modular installation		
fastening method bus-mounting	No		
net weight	139 g		
Approvals Certificates			
General Product Approval	Test Certificates	Marine / Shipping	other



[Confirmation](#)

[Special Test Certificate](#)



[Miscellaneous](#)

other	Railway	Environment
-------	---------	-------------

[Confirmation](#)

[Miscellaneous](#)

[Confirmation](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

**Further information**

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NH3051>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NH3051>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NH3051](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NH3051)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

6/22/2021

