



safety keyswitch for Extension Units, safety operator control, 22 mm, round, plastic, latching, with 2 keys, 2 switch positions 0-1, in position 0 the key can be removed, 2 closing contacts, without inscription, (incl. printed circuit board with contact module), scope of supply: 1 keyswitch, 1 printed circuit board, 2 keys, including mounting accessories

General information	
Product type designation	Safety keyswitch for Extension Unit
Control elements	
Version of actuating element	2 switch positions (pos. 0 removal position)
Operating principle of the actuating element	Latching
Shape of actuating element	Round
Illuminant	No; Cannot be illuminated
Contact configuration	2 NO contacts
Installation type/mounting	
Mounting type	Threaded ring
Front mounting	Yes; Front plate attachment in an Extension Unit for 16:9 PRO devices
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption (rated value)	100 mA
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	No
Degree and class of protection	
IP (at the front)	IP65 (on front) to EN60529 and NEMA4
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; Only in combination with Extension Unit
cULus	Yes; Only in combination with Extension Unit
RCM (formerly C-TICK)	Yes; Only in combination with Extension Unit
Suitable for safety functions	Yes; TÜV IEC 60947-5-x
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 500 m
Relative humidity	
• Operation, max.	90 %
• Condensation permissible	No
Mechanics/material	
Material	

• Plastic	Yes
Material of the actuating element	plastic
Material of the front ring	plastic
Enclosure color (front)	gray
Color of the front ring	Silver metallic
<b>Service life</b>	
• Number of operating cycles, keys	50 000
<b>Dimensions</b>	
Height of housing front	45.1 mm
Mounting diameter	22.3 mm
<b>Weights</b>	
Weight (without packaging)	50 g
Weight (with packaging)	100 g
<b>Scope of supply</b>	
Delivery quantity in pieces	1; Including 2 keys
<b>Other</b>	
Target devices	suitable for Extension Units of the 16:9 HMI/IPC PRO devices as of TIA Portal V16 (refer to manual)
Note:	configurable as of TIA Portal V16
<b>Usable in the following products</b>	
• Product 1	<a href="#">6AV7674-1LA31-0AA0</a>
• Product 2	<a href="#">6AV7674-1LA41-0AA0</a>
• Product 3	<a href="#">6AV7674-1LA51-0AA0</a>
• Product 4	<a href="#">6AV7674-1LA61-0AA0</a>
• Product 5	<a href="#">6AV7674-1LA32-0AA0</a>
• Product 6	<a href="#">6AV7674-1LA42-0AA0</a>
• Product 7	<a href="#">6AV7674-1LA52-0AA0</a>
• Product 8	<a href="#">6AV7674-1LA62-0AA0</a>
• Product 9	<a href="#">6AV7674-1LA33-0AA0</a>
• Product 10	<a href="#">6AV7674-1LA43-0AA0</a>
• Product 11	<a href="#">6AV7674-1LA53-0AA0</a>
• Product 12	<a href="#">6AV7674-1LA63-0AA0</a>

last modified:

8/2/2023 