



Figure similar

Complete unit combination 22 mm metal shiny round illuminated pushbutton momentary with flat button with holder with integ. LED, 24V AC/DC screw terminal, 1 NO blue

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Illuminated pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Metal, shiny, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	blue
shape of the actuating element	round
product component front ring	No
material of the front ring	metal
color of the front ring	chrome
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibitance (Date)	03/01/2017
Net Weight	87.2 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm
Approvals Certificates	
General Product Approval	other



[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6163-0DB50-1BA0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6163-0DB50-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6163-0DB50-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6163-0DB50-1BA0&lang=en



last modified:

4/3/2025