



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Nylo66, UL94V-0

| 编 号 | 尺寸 (mm) | |
|-----------|---------|-------|
| | A | B |
| A1251-02Y | 1.25 | 4.25 |
| A1251-03Y | 2.50 | 5.50 |
| A1251-04Y | 3.75 | 6.75 |
| A1251-05Y | 5.00 | 8.00 |
| A1251-06Y | 6.25 | 9.25 |
| A1251-07Y | 7.50 | 10.50 |
| A1251-08Y | 8.75 | 11.75 |
| A1251-09Y | 10.00 | 13.00 |
| A1251-10Y | 11.25 | 14.25 |
| A1251-11Y | 12.50 | 15.50 |
| A1251-12Y | 13.75 | 16.75 |
| A1251-20Y | 23.75 | 26.75 |

| | | | | | | | | | | | | | | | | |
|-------------|---------------------|------------|-------------------|-------------|---------------|-------------|----------------|----------------|------------|--------------|-------------|--------|-----------------|-------------|----|-------------------|
| 制图 DRAWN | 变更内容 DESCRIPTION | 日期 DATE | GENERAL TOLERANCE | | 制图 DRAWING | 黄彬 | | 料号 PART NO. | HX 1.25-5Y | 版本 REV. A | | | | | | |
| | | | X.±0.25 | X.*±2' | | 审核 CHECK | 张伟 | | | | 品名 TITLE | 压线端子胶壳 | 页次 SHEET 1/1 | | | |
| | | | .X±0.20 | .X*±1' | | | 核准 APPROVAL | | | | | | | 罗小春 | | 客户料号 CUTM. NO. |
| | | | .XX±0.15 | .XX*±0.5' | | | | | | | | | | 单位 UNITS | MM | |
| .XXX±0.10 | .XXX*±0.5' | | | 深圳市韩下电子有限公司 | | | | | | | | | | | | |