T4030014031-000 - ACTIVE

M8 Connector

TE Internal #: T4030014031-000 Wire-to-Panel, 3 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M8 Connector, Standard Circular Connectors

View on TE.com >

Connectors > Circular Connectors > Standard Circular Connectors > M8 Panel Mount Solder Cups



Connector System: Wire-to-Panel

Connector Mounting Type: Panel Mount

Number of Positions: 3

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

All M8 Panel Mount Solder Cups (8)



Features

Prod	uct [¬]	Гуре	Features

Product Type	Connector Assembly	
Accessory Color	Black	
Assembly Requirement	Factory Assembled	
Assembly Type	Electrical Connector	
Circular Connector Shell Type	Metal-Shell	
Connector Product Type	Connector Assembly	
Connector System	Wire-to-Panel	
Sealable	Yes	
Connector & Contact Terminates To	Wire & Cable	
Circular Connector Type	Plug	
Shell Type	Metal	
Configuration Features		
Keying & Polarized Position Locations	A	

Wire-to-Panel, 3 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M8 Connector, Standard Circular Connectors



Factory Installed Backshell	No
Keying	A
Number of Positions	3
Number of Power Positions	0
Number of Signal Positions	3
Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	60 VAC
Body Features	
Peripheral Seal Material	Silicone
Environmental Protection	IP67
O-Ring Material	Silicone
Environmental Protection Type	Sealed
Shell Plating Material	Nickel
Shell Base Material	Copper Alloy
Circular Connector Insulation Material Type	Polyamide 67 GF30

Contact Features

Contact Current Rating (Max)	3 A
Reverse Gender	Yes
Circular Connector Contact Type	Pin
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Polarization Code	A
Mating Alignment Type	Keyed
Housing Features	
Circular Connector Shell Size	12.6
Dimensions	
Wire Size	.25 – .75 mm²
Usage Conditions	
IP Dust Sealing Level	6
IP Water Sealing Level	IP67

Wire-to-Panel, 3 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M8 Connector, Standard Circular Connectors



Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]	
Operation/Application		
Circuit Application	Signal	
Shielded	No	
Industry Standards		
UL Flammability Rating	UL 94HB	
Packaging Features		
Packaging Quantity	1	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant with Exemptions	
EU RoHS Directive 2011/65/EU EU ELV Directive 2000/53/EC	Compliant with Exemptions Compliant with Exemptions	

Halogen Content

Solder Process Capability

SVHC > Threshold:

Pb (4% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Low Halogen - contains Br or Cl > 900

ppm.

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

Wire-to-Panel, 3 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M8 Connector, Standard Circular Connectors





Also in the Series | M8 Connector



Customers Also Bought



TE Part #4-1481303-9	TE Part #5-1481303-0	TE Part #5-1481303-1	TE Part #7-1481301-1
ANVIL - FOIL	CONTACT GUIDE	ANVIL - WIRE	WIRE CRIMPER TE

TE Part #7-1481301-4	TE Part #7-1481304-4
DOWN DEVICE	WIRE CRIMPER IEE

Wire-to-Panel, 3 Position, Sealable, Wire & Cable, Signal, Panel Mount, Reverse Gender, Nickel, M8 Connector, Standard Circular Connectors



Documents

Product Drawings M8.MLE.PNLREAR.3POS.STR

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_T4030014031-000_A.2d_dxf.zip

English

Customer View Model ENG_CVM_CVM_T4030014031-000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4030014031-000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages M8 / M12 Connector System Catalog

English

Product Specifications Application Specification

English

Application Specification

English

Agency Approvals UL

English