

2400089

https://www.phoenixcontact.com/us/products/2400089

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Program and configuration memory for extending the internal Flash memory, plug-in, 2GB, with a function block library for webMI from atvise[®]. For additional licensed function blocks, please refer to the documentation

Product description

Program and configuration memory for storing the application programs and other files in the file system of the PLC, with license for using the webMI functionality from atvise. A license key for activating further function block libraries is also included. Individual function blocks from Phoenix Contact, such as those from the SQL and SNMP library or Resy+, are licensed. This means that a fee is charged for each controller on which licensed function blocks are used. The blocks check the license stored on the controller during runtime and enable themselves or run for a limited time in demo mode. Examples of licensed function blocks:• Basic control functions for PID controllers with delay time constant in the D component• Data transfer between the controller and SQL database with event-driven access to tables by means of SQL communication and Data Manipulation Language (DML)• IT library for sending e-mails with the SMTP function, with DHCP client, DNS, and an FTP client function• Secure, event-oriented, and inexpensive monitoring of all distributed plants via Ethernet as well as via serial interfaces The webMI functionality can only be used in conjunction with the atvise Builder 2.5 software and class 1x1 controllers as of firmware 4.30 or the AXC 1050 as of firmware 2.10. Please observe the specified performance data of your controller(s) and check that it/they are suitable for your application. For users who do not wish to use the webMI functionality, the program and configuration memory is also available without a license as an option.

Your advantages

- · License key for webMI from atvise[®] with function block libraries
- · For storing application programs and other files in the file system of the PLC
- Program and configuration memory, plug-in, for webMI from atvise[®]_' with license key for function block libraries.

Commercial data

Item number	2400089
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRAAZA
Catalog page	Page 55 (C-6-2019)
GTIN	4046356940382
Weight per piece (including packing)	9.2 g
Weight per piece (excluding packing)	8.5 g
Country of origin	DE



2400089

https://www.phoenixcontact.com/us/products/2400089

Technical data

Product properties

Product type	Storage medium
Application	webMI from atvise [®]
Mounting position	vertical
Electrical properties	
Maximum power dissipation for nominal condition	0.165 W
Supply	
Supply voltage	3.3 V DC
Supply voltage range	2.7 V DC 3.6 V DC

Material specifications

Typical current consumption

Housing material	Plastic
riousing material	Flasiic

typ. 50 mA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C 85 °C	
---------------------------------	--------------	--

Mounting

Mounting position	vertical
-------------------	----------



2400089

https://www.phoenixcontact.com/us/products/2400089

Classifications

UNSPSC 21.0

	\sim	1 / 0	C
_		\perp A \circ	

	ECLASS-11.0	27242212
Ε٦	ГІМ	
	ETIM 8.0	EC000192
U	NSPSC	

32101600



2400089

https://www.phoenixcontact.com/us/products/2400089

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(c)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



2400089

https://www.phoenixcontact.com/us/products/2400089

Accessories

AXC 1050 XC - Controller

2701295

https://www.phoenixcontact.com/us/products/2701295



Axiocontrol for the direct control of Axioline I/Os. With 2 Ethernet interfaces, extended temperature range, and programming options according to IEC 61131-3. Complete with connector connector and marking field.

AXC 1050 - Controller

2700988

https://www.phoenixcontact.com/us/products/2700988



Axio control for direct open-loop control of Axioline I/Os. With 2 Ethernet interfaces and programming capabilities according to IEC 61131-3. Complete with connector connector and labeling field.

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com