

isc Triacs


BTA08-600C

FEATURES

- With TO-220AB insulated package
- Suitables for general purpose applications where gate high sensitivity is required. Application on 4Q such as phase control and static switching.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	UNIT
V_{DRM}	Repetitive peak off-state voltage	600	V
V_{RRM}	Repetitive peak reverse voltage	600	V
$I_{T(\text{RMS})}$	RMS on-state current (full sine wave) $T_j=105^\circ\text{C}$	8	A
I_{TSM}	Non-repetitive peak on-state current $t_p=20\text{ms}$	80	A
T_j	Operating junction temperature	110	$^\circ\text{C}$
T_{stg}	Storage temperature	-45~150	$^\circ\text{C}$
$R_{th(j-c)}$	Thermal resistance, junction to case	2.5	$^\circ\text{C}/\text{W}$
$R_{th(j-a)}$	Thermal resistance, junction to ambient	60	$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS		MAX	UNIT
I_{RRM}	Repetitive peak reverse current	$V_R=V_{RRM}$, $V_R=V_{RRM}$, $T_j=110^\circ\text{C}$		0.01 0.5	mA
I_{DRM}	Repetitive peak off-state current	$V_D=V_{DRM}$, $V_D=V_{DRM}$, $T_j=110^\circ\text{C}$		0.01 0.5	mA
I_{GT}	Gate trigger current	I	$V_D=12\text{V}$; $R_L=30\Omega$		25
		II			25
		III			25
		IV			50
I_H	Holding current	$I_{GT}=0.1\text{A}$, Gate Open		25	mA
V_{GT}	Gate trigger voltage all quadrant	$V_D=12\text{V}$; $R_L=30\Omega$		1.3	V
V_{TM}	On-state voltage	$I_T=11\text{A}$; $t_p=380\mu\text{s}$		1.55	V