

PCB LAYOUT

Specifications:

规格:

1.Voltage rating:250VAC/DC

额定电压: 250V AC/DC

2.Current rating:3A AC/DC

额定电流: 3A AC/DC

3. Withstanding voltage: 500V AC/minute

耐受电压: $\geq 500V$ AC/分钟

4. Temperature range: -55°C-+105°C

温度范围: -55°C - $+105^{\circ}\text{C}$

5. Insulation resistance: 1000MΩMIN

绝缘电阻: $\geq 1000\text{M}\Omega$

6.Contact resistance:30mΩMax

接触电阻: $\geq 30\text{m}\Omega$

Materialai:

材料:

7.Rubber core:PBT UL94V-0

胶芯: PBT UL94V-0

8.The iron shell:SPCC Nivkel Plating/Tin Plating/Gold Plating

铁壳: SPCC, 镀镍/镀锡/镀金

B、成品不能有弯针，R角不一致等不良。

X05 44 W X X X X A

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Series N0.

② Row No.Pin No.XX-44

③ Welding Board Angle :W-Male

(4) T: Traditional C: Car-pin

⑤ Planting Category: 1:Gold 1u ;2:Gold 2u; 3:Gold 3u ;4:Gold 5u; 5:Gold 15u;
6:Gold 30u ;7:Terminal half- Gold Bright Tin;8:Terminal half- Gold 2u Bright

9: Terminal half- Gold 3u Bright Tin;10: Terminal half- Gold 5u Bright Tin

11: Terminal half- Gold 15u Bright Tin; 12: Terminal half- Gold 30u Bright

13: Terminal half- Gold Matte Tin; 14: Terminal half- Gold 2u Matte Tin
15: Terminal half- Gold 2u Matte Tin; 16: Terminal half- Gold 2u Matte Tin


15:Terminal half- Gold 3u Matte Tin;16:Terminal half- Gold 5u Matte Tin
17:Terminal half- Gold 15u Matte Tin;18:Terminal half- Gold 30u Matte Tin

⑥ Color: B-BLACK W-White BL-Blue

⑦ 1:TYPE-1; 2:TYPE-2; 5:TYPE-5;

⑧ Specific symbol

0.0000

铆合方式	TYPE-1: riveting (铆合)	TYPE-2: Front riveted solid nut (前铆实心螺母)	TYPE-7: Rear riveted harpoon (后铆鱼叉)	TYPE-5: Riveted harpoon lock screw (铆鱼叉锁螺钉)
图示				

DSND		SCALE: N/A	MODEL TYPE: D-USB		
DWN		VIEW: 	PART NO.: X0544WXXXXA		
CHKD		UNIT: mm/in	DWG NO.: X-X0544WXXXXA		
APPD		SIZE: A4			
PRECISION CO.,LIMITED			WEIGHT	SHEET 1/1	REVISION A0

					ANGLAR	±5°
Δ x					L ≤ 4	±0.2
Δ x					4 < L ≤ 16	±0.3
Δ x					16 < L ≤ 63	±0.4
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5
REVISIONS						UNSPECIFIED TOLERANCES
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						