

Product information G 30 A 3 M grau/grey

Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:G 30 A 3 M grau/grey

G 30 A 3 M grau/grey

400
(GOD)

	Surface mounted connector for printed circuit boards with solder contacts
Delivery informations	
Availability	available
Product description	
Description	Surface mounted connector for printed circuit boards with solder contacts
Туре	G 30 A 3 M grau/grey
Order No.	931 700-106
Type of contact	blade contacts
Number of contacts	3 + PE
Standard	DIN VDE 0627 / IEC 61984
Housing Color	grey
Technical data	
Pin dimensions	2.8 mm x 0.8 mm
Rated voltage	AC/DC 250 V
Rated current	10 A
Contact resistance	<= 4 m0hm
Type of termination	solder (solder tabs for printed circuits)
Material	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
Environmental conditions Environmental Conditions	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
Inflammability class	
Housing	94 HB
Contact bearer	94 HB
Approvals	
VDE	VDE
Packing unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Scope of delivery	1 surface mounted connector
Accessories to order separately	can be plugged into G 30 KW 3 F 2m, G 30 W 3 F grau/grey






Industrial Connecting Solutions:Rectangular Connectors:DIN VDE 0627 / IEC 61984 Connectors (G serie):Cable plug:G 30 A 3 M grau/grey https://www.e-catalog.beldensolutions.com:443/link/57078-24228-256261-24347-24349-36961/en/conf/uistate

Picture

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

