



PCB HOLE CONFIGURATION  
RECOMMENDED PANEL CUTDUTS

### Specifications

Impedance: 50 Ohms  
Frequency Range: DC~3G  
VSWR: 1.3MAX  
Working Voltage: 500V rms @ sea level  
Insulation Resistance: 5000 Ohms min  
Temperature Range: -55°C TO +155°C  
Relative Temperature:  $\leq 95\%$  (40°C  $\pm 2^\circ$  C)  
Drawings products are in line with ROHS standards

#### NOTE:

DRAWN	Zelin Zhang	2012/11/10
CHECKED		

Tolerance	0-6 6-30 30-120	$\pm 0.15$ $\pm 0.20$ $\pm 0.5$
View	Angular	$\pm 2^\circ$

UNIT	MM
------	----

Name: **Dosin Industrial(H.K)Co.Ltd**  
**Dosin Hardware Electronics Co.,Ltd**  
 东莞市德奈五金电子有限公司  
 E-mail: dosin2005@163.com  
 dosin2005@dosin-china.com  
 Web: http://www.dosin.com.cn  
 TEL: (0086) 769-81153906  
 FAX: (0086) 769-81873836

APPROVALS	John	12/04.2012
-----------	------	------------

SCALE	1:1
-------	-----

SIZE	A	Product NO.	BNC CONNECTOR DNN
Date/Time	2012/11/02	CAD FILE	DOSIN-801-0050
		D/company drawings/BD	

3	BODY	ZINC	NICKEL	1
2	INSULATOR	PDM	WHITE	1
1	PIN	BRASS	GOLD	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY