


Surface Mount Common Mode Chokes


Model HM67 Series

Features

- Operating Temperature Range -40°C to +125°C
- Temperature Rise, Maximum 40°C
- Dielectric Withstanding Voltage 300Vdc
- RoHS Compliant



Schematics



Specification

Part Number	Terminals	Common Mode Inductance @100 kHz - 0.1 V (1-4 or 2-3) μ H	Inductance Leakage @100 kHz - 0.1 Vrms (1-4) ⁽¹⁾ Typ. μ H	Rated Current mA	DCR ⁽²⁾ Max Ω	Marking Code	Figure
HM67-B5R0LF	1-4, 2-3	5.0 \pm 30%	0.08	1000	0.12	A	1
HM67-B110LF	1-4, 2-3	11.0 \pm 30%	0.10	500	0.15	B	1
HM67-S250LF	1-4, 2-3	25.0 \pm 30%	1.60	500	0.18	C	1
HM67-B510LF	1-4, 2-3	51.0 \pm 30%	1.90	500	0.10	D	1
HM67-S510LF	1-4, 2-3	51.0 \pm 30%	2.80	500	0.25	E	1
HM67-B471LF	1-4, 2-3	470.0 \pm 30%	0.80	500	0.28	F	1
HM67-B102 ⁽³⁾ LF	1-4, 2-3	1000.0 +50%, -30%	0.16	500	0.30	G	1
HM67-B222 ⁽³⁾ LF	1-4, 2-3	2200.0 +50%, -30%	0.16	400	0.42	H	1
HM67-B472 ⁽³⁾ LF	1-4, 2-3	4700.0 +50%, -30%	0.24	200	0.67	I	1
HM67-10510LF	1-4, 2-3	51.0 \pm 30% ⁽⁴⁾	2.40 ⁽⁴⁾	200	0.403	0510	2

- Notes: (1) Leakage inductance is measured with pin 2 & 3 shorted.
 (2) DC resistance is measured at 25°C.
 (3) Maximum operating temperature is +85°C.
 (4) Common mode inductance & leakage inductance of HM67-10510LF are measured at 100 kHz, 0.05V

Packaging


Standard:	Embossed Tape and Reel		
	Reel:	Diameter:	
		Figure 1 & 2	= 13" (330.2mm)
		Capacity:	Figure 1
Figure 2			= 2000 Units

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
 All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


Model HM67 Series

Ordering Information



Inductance Code:
 First 2 digits are significant.
 Last digit denotes the number of trailing zeros.
 For values below 10µH, "R" denotes the decimal point.

Outline Dimensions (Inch/mm)




General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
 All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


Electrical Characteristics @ 25°C

(A) Attenuation vs. Frequency Graphs


HM67-B5R0LF




HM67-S250LF



HM67-B110LF




HM67-B510LF



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Electrical Characteristics @ 25°C (Continued)




General Note


TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Electrical Characteristics @ 25°C (Continued)

(B) Insertion Loss vs. Frequency Graph



(C) Current Derating Curve



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TT Electronics:

[HM67-3216-601LFTR7](#) [HM67-3216-900LFTR7](#) [HM67-3216-222LFTR7](#) [HM67-3216-102LFTR7](#) [HM67-3216-161LFTR7](#) [HM67-3216-261LFTR7](#) [HM67-S510LFTR13](#) [HM67-10510LFTR](#) [HM67-B471LFTR13](#) [HM67-B510LFTR13](#) [HM67-B110LFTR13](#) [HM67-S250LFTR13](#) [HM67-B222LFTR13](#) [HM67-B5R0LFTR13](#) [HM67-B472LFTR13](#) [HM67-B102LFTR13](#)