

### General Description

The Sanrise SRT04N024LD56TR-GS is a low voltage power MOSFET, fabricated using advanced split gate trench technology. The resulting device has extremely low on resistance, low gate charge and fast switching time, making it especially suitable for applications which require superior power density and synchronous rectification.

The SRT04N024LD56TR-GS break down voltage is 40V and it has a high rugged avalanche characteristics.

The SRT04N024LD56TR-GS is available in PDFN5\*6 package.


### Features

- Ultra Low  $R_{DS(ON\_TYP)} = 2.1m\Omega @ V_{GS} = 10V$ .
- Ultra Low Gate Charge,  $Q_g = 40nC$  typ.
- Fast switching capability
- Robust design with better EAS performance
- EMI Improved
- Non-automotive Qualified

### Application

- Server/Telecom
- High Power Supply
- E-Tools
- Motor Driver
- BMS

### Ordering Information



### Symbol





Figure 1 Symbol of SRT04N024LD56TR-GS

### Package Type



PDFN5\*6

Figure 2 Package Type of SRT04N024LD56TR-GS

| Package | Part Number        | Marking ID      | Packing Type |
|---------|--------------------|-----------------|--------------|
| PDFN5*6 | SRT04N024LD56TR-GS | SRT04N024LD56GS | Tape & Reel  |

### Absolute Maximum Ratings

| Parameter   |                    | Symbol          | Rating     | Unit |
|---|--------------------|-----------------|------------|------|
| Drain-Source Voltage                                |                    | $V_{DSS}$       | 40         | V    |
| Gate-Source Voltage                                 |                    | $V_{GSS}$       | ±20        | V    |
| Continuous Drain Current, Silicon                   | $T_C=25^{\circ}C$  | $I_D$           | 132        | A    |
|   | $T_C=100^{\circ}C$ |                 | 59         |      |
| Continuous Drain Current, Silicon                   | $T_C=25^{\circ}C$  |                 | 132        |      |
| Pulsed Drain Current (Note 2)                       |                    | $I_{DM}$        | 528        | A    |
| Avalanche Energy, Single Pulse (Note 3)             |                    | $E_{AS}$        | 64         | mJ   |
| Avalanche Destructive Energy, Single Pulse (Note 4) |                    | $E_{AS\_Limit}$ | 400        | mJ   |
| Avalanche Energy, Repetitive (Note 2)               |                    | $E_{AR}$        | 0.2        | mJ   |
| Avalanche Current, Repetitive (Note 2)              |                    | $I_{AR}$        | 20.0       | A    |
| Continuous Diode Forward Current                    |                    | $I_S$           | 80         | A    |
| Diode Pulse Current                                 |                    | $I_{S,PULSE}$   | 240        | A    |
| Max Power Dissipation                               |                    | $P_D$           | 78.1       | W    |
| Operating Junction Temperature                      |                    | $T_J$           | 150        | °C   |
| Storage Temperature                                 |                    | $T_{STG}$       | -55 to 150 | °C   |
| Lead Temperature (Soldering, 10 sec)                |                    | $T_{LEAD}$      | 260        | °C   |

Note:

- Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.
- Repetitive Rating: Pulse width limited by maximum junction temperature
- $I_{AS}=16.0A$ ,  $V_{DD}=20V$ ,  $R_G=25\Omega$ , Starting  $T_J=25^{\circ}C$
- $I_{AS\_Limit}=40A$ ,  $V_{DD}=20V$ ,  $R_G=25\Omega$ , Starting  $T_J=25^{\circ}C$

### Thermal Resistance

| Parameter                               |         | Symbol     | Min | Typ | Max | Unit |
|---|---------|------------|-----|-----|-----|------|
| Thermal Resistance, Junction-to-Case    | PDFN5*6 | $R_{thJC}$ |     |     | 1.6 | °C/W |
| Thermal Resistance, Junction-to-Ambient | PDFN5*6 | $R_{thJA}$ |     |     | 50  |      |





**Electrical Characteristics**
 $T_J = 25^\circ\text{C}$ , unless otherwise specified.





| Parameter   | Symbol        | Test Conditions                                  | Min | Typ  | Max  | Unit    |
|---|---------------|--|-----|------|------|---------|
| <b>Statistic Characteristics</b>                                  |               |  |     |      |      |         |
| Drain-Source Breakdown Voltage                                    | $BV_{DSS}$    | $V_{GS}=0V, I_D=250\mu A$                        | 40  |      |      | V       |
| Zero Gate Voltage Drain Current                                   | $I_{DSS}$     | $V_{DS}=40V, V_{GS}=0V$                          |     |      | 1    | $\mu A$ |
| Gate-Body Leakage Current   | Forward       | $I_{GSSF}, V_{GS}=20V, V_{DS}=0V$                |     |      | 200  | nA      |
|   | Reverse       | $I_{GSSR}, V_{GS}=-20V, V_{DS}=0V$               |     |      | -200 |         |
| Gate Threshold Voltage  | $V_{GS(TH)}$  | $V_{DS}=V_{GS}, I_D=0.25mA$                      | 1.2 | 1.8  | 2.4  | V       |
| Static Drain-Source On-Resistance                                 | $R_{DS(ON)}$  | $V_{GS}=10V, I_D=35A$                            |     | 2.1  | 2.4  | mΩ      |
|   |               | $V_{GS}=4.5V, I_D=15A$                           |     | 4.2  | 6.5  |         |
| Gate Resistance   | $R_G$         | $f=1MHz, \text{Open Drain}$                      |     | 1.4  |      | Ω       |
| <b>Dynamic Characteristics</b>                                    |               |  |     |      |      |         |
| Input Capacitance   | $C_{ISS}$     | $V_{DS}=20V, V_{GS}=0V, f=1MHz$                  |     | 2.8  |      | nF      |
| Output Capacitance  | $C_{OSS}$     |  |     | 762  |      | pF      |
| Reverse Transfer Capacitance                                      | $C_{RSS}$     |  |     | 48   |      | pF      |
| Effective output capacitance, energy related <small>NOTE5</small> | $C_{O(er)}$   | $V_{GS}=0V, V_{DS}=0\dots 20V$                   |     | 1.2  |      | nF      |
| Effective output capacitance, time related <small>NOTE6</small>   | $C_{O(tr)}$   |  |     | 1.5  |      |         |
| Turn-on Delay Time  | $t_{d(on)}$   | $V_{DD}=20V, I_D=35A, R_G=1.6\Omega, V_{GS}=10V$ |     | 9    |      | ns      |
| Rise Time   | $t_r$         |  |     | 31   |      |         |
| Turn-off Delay Time   | $t_{d(off)}$  |  |     | 34   |      |         |
| Fall Time   | $t_f$         |  |     | 7    |      |         |
| <b>Gate Charge Characteristics</b>                                |               |  |     |      |      |         |
| Gate to Source Charge   | $Q_{gs}$      | $V_{DD}=20V, I_D=35A, V_{GS}=0 \text{ to } 10V$  |     | 6.1  |      | nC      |
| Gate to Drain Charge  | $Q_{gd}$      |  |     | 4.7  |      |         |
| Gate Charge Total   | $Q_g$         |  |     | 40   |      |         |
| Gate Plateau Voltage  | $V_{plateau}$ |  |     | 2.4  |      | V       |
| Gate Charge Total, sync FET                                       | $Q_g$         | $V_{DD}=0.1V, V_{GS}=0 \text{ to } 10V$          |     | 38   |      | nC      |
| <b>Reverse Diode Characteristics</b>                              |               |  |     |      |      |         |
| Drain-Source Diode Forward Voltage                                | $V_{SD}$      | $V_{GS}=0V, I_{SD}=35A$                          |     | 0.84 | 1.0  | V       |
| Reverse Recovery Time   | $t_{rr}$      | $V_R=20V, I_F=35A, dI_F/dt=100A/\mu s$           |     | 52   |      | ns      |
| Reverse Recovery Charge   | $Q_{rr}$      |  |     | 91   |      | nC      |
| Peak Reverse Recovery Current                                     | $I_{rrm}$     |  |     | 3.5  |      | A       |


Note:

- $C_{O(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 32V
- $C_{O(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 32V


**Typical Performance Characteristics**

|   |  |
|---|--|
| <p>Figure 3: Power Dissipation</p>  <p><math>P_{tot}=f(T_C)</math></p>          | <p>Figure 4: Max. Transient Thermal Impedance</p>  <p><math>Z_{(th)JC}=f(t_p)</math>; parameter: <math>D=t_p/T</math></p>       |
| <p>Figure5: Drain Current</p>  <p><math>I_D=f(T_C); V_{GS} \geq 10V</math></p> | <p>Figure6: Typ. Output Characteristics</p>  <p><math>I_D=f(V_{DS}); T_j=25^\circ C</math>; parameter: <math>V_{GS}</math></p> |


**Figure7: Typ. Drain-Source On-State Resistance**

 $R_{DS(ON)}=f(I_D); T_j=25^\circ C$ ; parameter:  $V_{GS}$ 
**Figure8: Typ. Transfer Characteristics**

 $I_D=f(V_{GS}); |V_{DS}|>2|I_D|R_{DS(on)max}$ ; parameter:  $T_j$ 
**Figure9: Typ. Forward Transconductance**

 $g_{fs}=f(I_D); T_j=25^\circ C$ 
**Figure10: Typ. Drain-Source On-State Resistance**

 $R_{DS(ON)}=f(T_j); I_D=35A; V_{GS}=10V$

**Figure 11: Typ. Gate Threshold Voltage**



$$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}; I_{DS} = 250\mu A$$

**Figure 12: Typ. Gate Charge**



$$V_{GS} = f(Q_{gate}), I_D = 35A \text{ pulsed}$$

**Figure 13: Drain-Source Leakage Current**



$$I_{DSS} = f(V_{DS}); V_{GS} = 0V; \text{parameter: } T_j$$

**Figure 14: Forward Characteristics of Reverse Diode**



$$I_F = f(V_{SD}); \text{parameter: } T_j$$

**Figure 15: Avalanche Energy**








$$E_{AS}=f(T_j); I_D=20.0A; V_{DD}=20V$$

**Figure 16: Typ. Capacitances**


$$C=f(V_{DS}); V_{GS}=0; f=1MHz$$



**Figure 17: Coss Stored Energy**



$$E_{OSS}=f(V_{DS})$$

**Test Circuits**
**1. Gate Charge Test Circuit & Waveform**

**2. Switch Time Test Circuit**

**3. Unclamped Inductive Switching Test Circuit & Waveforms**





4. Test Circuit and Waveform for Diode Characteristics



**Mechanical Dimensions**
**PDFN5\*6-8 (Package1)**
**Unit: mm**


| Symbol | Dimensions (mm) |       |      | Symbol | Dimensions (mm) |         |      |
|--------|-----------------|-------|------|--------|-----------------|---------|------|
|        | Min.            | Typ.  | Max. |        | Min.            | Typ.    | Max. |
| A      | 0.90            |       | 1.20 | E1     | 4.90            | 5.00    | 5.10 |
| b      | 0.30            | 0.40  | 0.50 | E2     | -               | 4.01    | -    |
| b1     | 0.20            | 0.30  | 0.40 | e      | -               | 1.27BSC | -    |
| c      | 0.20            | 0.25  | 0.35 | H      | 0.50            | 0.65    | 0.75 |
| D      | 5.90            | 6.05  | 6.20 | L      | 0.51            | 0.635   | 0.75 |
| D1     | 5.65            | 5.75  | 5.85 | L1     | -               | 0.15    | -    |
| D2     | -               | 3.475 | -    | θ      | -               | 10°     | -    |
| E      | -               | -     | 5.20 |        |                 |         |      |

**Mechanical Dimensions**
**PDFN5\*6-8 (Package2)**
**Unit: mm**


| Symbol | Dimensions(mm) |      |      |
|--------|----------------|------|------|
|        | Min.           | Typ. | Max. |
| A      | 0.90           |      | 1.20 |
| b      | 0.35           | 0.40 | 0.45 |
| c      | 0.21           | 0.25 | 0.34 |
| D      |                |      | 5.10 |
| D1     | 4.80           | 4.90 | 5.00 |
| D2     | 3.91           | 4.01 | 4.11 |
| e      | 1.17           | 1.27 | 1.37 |
| E      | 5.90           | 6.00 | 6.10 |
| E1     | 5.70           | 5.75 | 5.80 |
| E2     | 3.34           | 3.44 | 3.54 |
| H      | 0.51           | 0.61 | 0.71 |
| K      | 1.10           |      |      |
| L      | 0.51           | 0.61 | 0.71 |
| L1     | 0.06           | 0.13 | 0.20 |
| L2     |                |      | 0.10 |
| P      | 1.00           | 1.10 | 1.20 |
| θ      | 8°             | 10°  | 12°  |



Sanrise Technology Limited Company

<http://www.sanrise-tech.com>

#### **IMPORTANT NOTICE**

Shenzhen Sanrise Technology Co., LTD. reserves the right to make changes without further notice to any products or specifications herein. Shenzhen Sanrise Technology Co., LTD. does not assume any responsibility for use of any its products for any particular purpose, nor does Shenzhen Sanrise Technology Co., LTD. assume any liability arising out of the application or use of any its products or circuits. Shenzhen Sanrise Technology Co., LTD. does not convey any license under its patent rights or other rights nor the rights of others.

---

#### **Main Site:**

##### **- Headquarter**

Shenzhen Sanrise Technology Co., LTD.

A1206, Skyworth building, No. 008, gaoxinnan 1st Road,  
Gaoxin District, Yuehai street,, Nanshan District, ShenZhen,  
P.R.China

Tel: +86-755-22953335

Fax: +86-755-22916878

##### **- Shanghai Office**

Sanrise Technology Limited Company

Rm.401, Building B, No. 666, Zhangheng Road,  
Zhangjiang Hi-Tech Park, Shanghai, P.R.China

Tel: +86-21-68825918