1SNK908914R0000 V ACTIVE

ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK908914R0000

Jumper Bar, 4 Pole, Orange, Product Spacing 8 mm [.315 in], -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK, Terminal Block & Strip

Conducting Accessories

View on TE.com >



Connectors > Terminal Blocks & Strips > Terminal Block & Strip Accessories > Terminal Block & Strip Conducting Accessories











Conducting Accessory Type: Jumper Bar

Number of Poles: 4

PCB Mount Retention Type: Screwless

Primary Product Color: Orange
Product Spacing: 8 mm [.315 in]

Features

Product Type Features

Conducting Accessory Type	Jumper Bar
Configuration Features	
Number of Poles	4
Electrical Characteristics	
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	6000 V
Voltage Rating (CSA)	600 V
Current Rating (CSA)	42 A
Short-Time Withstanding Current Rating @ 1s	1200 A
Power Loss	1.8 W
Dielectric Withstanding Voltage (Max)	2200 V
Voltage Rating (IEC)	1000 V
Current Rating (UL)	42 A
Current Rating (IEC)	57 A



Body Features

Plastic & Resin Material Type	Polyamide
Product Weight	7.84 g[.235 oz]
Primary Product Color	Orange
Contact Features	
Contact Current Rating (Max)	57 A
Mechanical Attachment	
PCB Mount Retention Type	Screwless
Dimensions	
Product Depth	37.8 mm[1.488 in]
Product Width	8 mm[.315 in]
Product Height	3.6 mm[.142 in]
Product Spacing	8 mm[.315 in]
Usage Conditions	
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Industry Standards	

Product Compliance

IP Rating

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

IP20

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(320)




Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought





















TE Part #1SNA166722R2100 CC-S-INF-VL-6.6

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK908914R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK908914R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK908914R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

JB8-4-R2

English