

https://www.phoenixcontact.com/us/products/1409147

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Coated protective cover for the housing on the motor side



### Commercial data

Item number	1409147
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	AB01
Product key	ABLADE
Catalog page	Page 53 (C-2-2013)
GTIN	4046356619448
Weight per piece (including packing)	5.76 g
Weight per piece (excluding packing)	10.77 g
Customs tariff number	39235090
Country of origin	DE

PHENIX

1409147

https://www.phoenixcontact.com/us/products/1409147



### Technical data

#### Notes

Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	<ul> <li>The products are suitable for applications in plant, controller, and electrical device engineering.</li> </ul>
	<ul> <li>When operating the connectors in outdoor applications, they must be separately protected against environmental influences.</li> </ul>
	<ul> <li>Assembled products may not be manipulated or improperly opened.</li> </ul>
	<ul> <li>Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).</li> </ul>
	<ul> <li>When using the product in direct connection with third-party manufacturers, the user is responsible.</li> </ul>
	<ul> <li>For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li> </ul>
	<ul> <li>Ensure that the protective or functional ground has been properly connected.</li> </ul>
	• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	<ul> <li>Observe the corresponding technical data. You will find information:</li> <li>o On the product</li> <li>o On the packing label</li> <li>o In the supplied documentation</li> <li>o Online at phoenixcontact.com/products under the product</li> </ul>
	Only use tools recommended by Phoenix Contact
	<ul> <li>The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.</li> </ul>
	<ul> <li>Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products</li> </ul>
	Operate the connector only when it is fully plugged in.
	<ul> <li>Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the</li> </ul>



#### 1409147

https://www.phoenixcontact.com/us/products/1409147

sta	andards.
	Dbserve the minimum bending radius of the cable. Lay the block blo
am wa	The connector warms up in normal operation. Depending on the nbient conditions, the surface of the connector can continue to arm up. In this case, the user is responsible for posting arnings (e.g. DIN EN ISO 13732-1:2008-12).

#### Product properties

Product type	Protective cover
Product family	VARIOCON
Туре	МОТ

#### Dimensions

Dimensional drawing	
Width	63.8 mm
Height	27.25 mm
Length	6.2 mm

#### Material specifications

Seal material	TPE
Material, protective cover	PA

#### Environmental and real-life conditions


Ambient conditions	
Ambient temperature (operation)	-30 °C 100 °C



1409147

https://www.phoenixcontact.com/us/products/1409147

### Drawings



Dimensional drawing



https://www.phoenixcontact.com/us/products/1409147



### Classifications

#### ECLASS

ECLASS-12.0         27440208           ECLASS-13.0         27440208	ECLASS-11.0	27440208
ECLASS-13.0 27440208	ECLASS-12.0	27440208
	ECLASS-13.0	27440208

#### ETIM

	ETIM 9.0	EC002314
UN	NSPSC	
	UNSPSC 21.0	39121400



https://www.phoenixcontact.com/us/products/1409147



### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com