Note: This datasheet may be out of date.

Please download the latest datasheet of CSTCR6M14G53-R0 from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd.
https://www.murata.com/en-us/products/productdetail?partno=CSTCR6M14G53-R0

CSTCR6M14G53-R0












Appearance & Shape







MURATA's package technology expertise has enabled the development of the Chip CERALOCK(R) with built-in load capacitors. High-density mounting can be realized because of the small package and the elimination of the need for an external load capacitor.

Features

- 1. Oscillation circuits do not require external load capacitors.
- 2. Available in a wide frequency range.
- 3. Extremely small and have a low profile.
- 4. No adjustment is necessary for oscillation circuits.

Applications

Other Usage

Consumer/Industrial



Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Embossed Tape	3000

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: https://www.murata.com/

Last updated : 2019/02/24



Note: This datasheet may be out of date $\underline{ Please \ download \ the \ latest \ data sheet \ of \ CSTCR6M14G53-R0 \ from \ the \ of \ icial \ website \ of \ Murata \ Manufacturing} }$

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-us/products/productdetail?partno=CSTCR6M14G53-R0} \\$

CSTCR6M14G53-R0



Product Type	Ceramic Resonator (CERALOCK®)	
Series	CSTCR_G	
Frequency	6.144MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature Range	-20℃ to 80℃	
Frequency Shift by Temperature	+/-0.20% max.	
Frequency Aging	+/-0.10% max.	
Resonant Impedance (R1)	50ohm max.	
Built-in Load Capacitance(CL1/CL2)	15pF	
Shape	SMD	
Wash	Not available	
L x W (size)	4.5x2.0mm	

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/02/24