



**技术规格:**

**1:电性能**

- 1.1 额定电流: 1.8A
- 1.2 接触电阻: 30mΩ MAX
- 1.3 绝缘电阻: 1000MΩ MIN 500V DC
- 1.4 耐压测试: 500V AC

**2:机械性能**

- 2.1 插入力: 3.57kgf MAX
- 2.2 拔出力: 1.00kgf MIN
- 2.3 耐温性: 烤箱测试: 温度260±5℃, 时间3分钟

- 2.4 工作温度: -30℃~+80℃

**3:材质及表面处理:**

- 3.1 胶芯: LCP 黑色 UL94V-0
- 3.2 端子: C5191, 镍底, 镀金3.0μ”
- 3.3 外壳: C2680, 表面镀镍80μ”
- 3.4 符合ROHS的要求

RECOMMENDED P.C.B HOLE LAYOUT  
COMPONENT SIDE VIEW(TOLERANCE: +/-0.05)

德艺隆电子有限公司

名称	MICRO 5P 四脚平口有柱6.5MM	2018/02/15	吴晓涛	绘图	DRAW	General Tolerance	2018/02/15	吴晓涛
TITLE:	USB-MIR-D-034	2018/02/15	吴晓涛	设计	DESIGN	.X ±0.30 .XX ±0.20 .XXX ±0.10	2018/02/15	吴晓涛
料號	PART NO.	2018/02/15	金俊林	校核	CHECK	Angle Tolerance	2018/02/15	金俊林
圖號	DWG. NO.	SCALE	1:1	承認	APPRO.	.X' ±1.0° .XX' ±0.5° .XXX' ±0.2°	UNIT: mm	A4
								SHEET: 1 of 1