

**RESISTIVE POWER DIVIDER, 50 Ohm, BNC**

4901.01.A

**Properties**

- Very low return loss
- Broadband down to DC
- Effective solution to tap off a signal



<b>Material data</b>	
<b>Interface side 1</b>	BNC / jack (female)
Standard side 1	IEC 60169-8_MIL-STD-348A/301_CECC 22120
Center contact, material / plating	Copper Beryllium Alloy / Gold Plating (without Nickel underplating)
Outer contact, material / plating	Brass / SUCOPLATE (R) Plating
Body, material / plating	Brass / SUCOPLATE (R) Plating
Insulator, material	PFA / PTFE
<b>Interface side 2</b>	BNC / jack (female)
Standard side 2	IEC 60169-8_MIL-STD-348A/301_CECC 22120
Center contact, material / plating	Copper Beryllium Alloy / Gold Plating (without Nickel underplating)
Outer contact, material / plating	Brass / SUCOPLATE (R) Plating
Body, material / plating	Brass / SUCOPLATE (R) Plating
Insulator, material	PFA / PTFE
<b>Interface side 3</b>	BNC / jack (female)
Standard side 3	IEC 60169-8_MIL-STD-348A/301_CECC 22120
Center contact, material / plating	Copper Beryllium Alloy / Gold Plating (without Nickel underplating)
Outer contact, material / plating	Brass / SUCOPLATE (R) Plating
Body, material / plating	Brass / SUCOPLATE (R) Plating
Insulator, material	PFA / PTFE
<b>Electrical data</b>	
Impedance	50 Ω
Frequency frame	0 GHz to 2 GHz
Return loss typical	23.12 dB
Insertion loss typical	6 dB

**RESISTIVE POWER DIVIDER, 50 Ohm, BNC**

4901.01.A

<b>Electrical bands</b>			
	<b>Band 1</b>	<b>Band 2</b>	<b>Band 3</b>
Frequency range	0 GHz ... 0.5 GHz	0.5 GHz ... 1 GHz	1 GHz ... 2 GHz
Return loss	32.25 dB	29.41 dB	23.12 dB
VSWR max side 1	1.05	1.07	1.15
Amplitude tracking max	0.3 dB	0.2 dB	0.3 dB
Phase tracking max	3°	3°	3°

<b>Electrical remarks</b>	
Power rating	1 W at 70 °C ambient temperature. Linearly derated to 0 W at 130 °C ambient temperature.
Electrical remarks	Isolation: 6 dB nominal between two ports

<b>Mechanical data</b>	
Weight	0.065 kg

<b>Ordering Information Table</b>	
Item number	Item description
22550077	4901.01.A

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P1894 / Date of publication: 07.11.2023 / uncontrolled copy