




Part Number : [2127252080](#)

Product Description : Micro-One Terminal Position Assurance (TPA) Retainer, 8 Circuits, 2.00mm Pitch, Glow-Wire Capable, Natural

Series Number : 212725

Status : Active

Product Category : Connector Accessories



Documents & Resources

Drawings

[Drawing 2127252080_sd.pdf](#)

3D Models and Design Files

[2D Drawing DXF 2127252080.dxf](#)

[2D Drawing DXF \(PDF\) 2127252080.pdf](#)

[3D Model 2127252080_stp.zip](#)

Specifications


[Application Specification 2059790000-AS-000.pdf](#)

[Packaging Specification 2127259200-SPK-200.pdf](#)

[Product Specification 2059790000-PS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Accessories
Series	212725
Description	Micro-One Terminal Position Assurance (TPA) Retainer, 8 Circuits, 2.00mm Pitch, Glow-Wire Capable, Natural
Component Type	Terminal Position Assurance
Product Family	Micro-One Wire-to-Board Connector System
Product Name	Micro-One
UPC	193264613960

Agency

UL	E29179
----	--------

Physical

Circuits (Loaded)	8
Circuits (maximum)	8
Color - Resin	Natural
Lock to Mating Part	Yes
Material - Resin	Polyamide
Net Weight	115.280/mg
Number of Rows	1
Packaging Type	Bag
Temperature Range - Operating	-40° to +105°C

Use with Part(s)

Description	Part Number
Micro-One Single Row Receptacle Housings	<u>212724</u>

This document was generated on Sep 25, 2024