

Part Number : 15388210

Series Number : 70430 Product Category : FFC / FPC Connectors

Documents & Resources

Drawings Drawing 015388210_sd.pdf Packaging Design Drawing PK-70873-0001-001.pdf

3D Models and Design Files 3D Model 015388210_stp.zip

Specifications Product Specification PS-70430-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | (|
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Product Description : SL Single Row, Female, Version G Receptacle, 21 Circuits Status : Active Engineering Number : 70430-0160

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | FFC / FPC Connectors |
| Series | 70430 |
| Description | SL Single Row, Female, Version G Receptacle, 21 Circuits |
| Product Family | SL Modular Connectors |
| Product Name | SL |
| UPC | 800754591287 |

Agency

| CSA | LR19880 |
|-----|---------|
| UL | E29179 |

Electrical

| Current - Maximum per Contact | 1.0A, 2.0A |
|-------------------------------|------------|
| Voltage - Maximum | 250V |

Physical

| Actuator Type | N/A |
|--------------------------------|-----------------|
| Circuits (Loaded) | 21 |
| Color - Resin | Black |
| Contact Position | N/A |
| Durability (mating cycles max) | 25 |
| Flammability | 94V-0 |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | Polyester Alloy |
| Net Weight | 3.100/g |
| Number of Rows | 1 |

| Orientation | Vertical |
|-------------------------------|----------------|
| Packaging Type | Tube |
| PC Tail Length | 3.30mm |
| PCB Mounting | N/A |
| PCB Retention | None |
| PCB Thickness - Recommended | 1.60mm, 2.40mm |
| Pitch - Mating Interface | 2.54mm |
| Pitch - Termination Interface | 2.54mm |
| Plating min - Mating | 3.810µm |
| Plating min - Termination | 1.905µm |
| Polarized to PCB | N/A |
| Stackable | Yes |
| Temperature Range - Operating | -40° to +105°C |
| Wire/Cable Type | FFC/FPC |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|--------------|
| SL Single Row Housing Panel Mounts | <u>70018</u> |
| SL Single Row Crimp Housings | <u>70107</u> |
| SL Vertical Single Row Headers | 70541 |
| SL Vertical Single Row Headers | 70543 |
| SL Vertical Single Row Headers | 70545 |
| SL Right-Angle Single Row Headers | 70551 |
| SL Right-Angle, Single Row, Low Profile Headers | 70553 |
| SL Right-Angle Single Row Headers | 70555 |
| SL Right-Angle, Single Row, Low Profile, Surface Mount Headers | 70634 |
| SL Vertical, Single Row, Surface Mount Headers | 74099 |

This document was generated on Sep 17, 2024