

Isolator Series 120V 1000W Isolation Transformer-Based Power Conditioner, 4 Outlets

MODEL NUMBER: IS1000



Description

Get complete protection for sensitive devices and prevent power disruption with Tripp Lite's Isolator IS1000 Isolation Transformer. Featuring an internal isolation transformer with Faraday Shield, the IS1000 completely isolates equipment from line noise that can cause incremental but devastating equipment damage. Its 680-joule surge suppression rating protects equipment from surges and spikes caused by utility power disruptions and the operation of nearby equipment on the same circuit. Its 6-ft. power cord allows for flexibility during installation, while its built-in circuit breaker prevents dangerous circuit overloads. Its 1000-watt capacity allows it to be used with a variety of sensitive equipment. Its 4 widely spaced NEMA 5-15R outlets accommodate bulky transformers, and its lighted power switch offers convenient, one-touch power control. For peace of mind, the IS1000 features a rugged, all-metal housing.

Features

- Tripp Lite Isolator series isolation transformer-based power conditioners offer complete line isolation, continuous noise filtering and enhanced common mode surge suppression
- Supports combined loads up to 1000 watts continuous/8.3A at 120V
- Isolation transformer with Faraday Shield offers 100% isolation from the input AC line
- Neutral to ground bonding at the secondary eliminates common mode noise and provides an isolated ground reference for sensitive equipment
- Isolation transformer design serves as an inexpensive alternative to the installation of dedicated circuits and site electrical upgrades
- Removes EMI/RFI noise, utility switching transients, background spikes and power problems generated by other on-site loads, utility grid-switching and lightning related surges
- Line isolation with additional surge suppression components offer continuous line filtering of a full range of power line noise in all modes
- Continuous transformer filtering with no wearable parts reduces surges in the worst of power

Highlights

- Completely isolated protection with enhanced surge suppression and noise filtering
- Faraday Shield offers 100% isolation from the input AC line
- 1000-watt continuous capacity with 4 NEMA 5-15R outlets
- 680-joule surge suppression rating
- 6-ft. power cord with NEMA 5-15P plug
- 9A circuit breaker provides overload protection
- Convenient, lighted power switch for simple power control
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

- IS1000 Isolation Transformer
- Owner's Manual



environments to harmless levels

- Includes 4 widely-spaced NEMA5-15R output receptacles, 6 ft power cord, circuit breaker overload protection and lighted power switch
- Rugged all-metal housing ships ready for upright tower or wallmount installation

Specifications

OVERVIEW	
Efficiency	96%
Let-through Voltage (Combination Wave)	L-N: <130V L-G: <10V N-G: <0.5V IEEE C62.41 Cat. B
Let-through Voltage (Ring Wave)	L-N: <10V L-G: <10V N-G: <0.5V IEEE C62.41 Cat. A
Nominal Voltage / Frequency	120V / 60Hz
Over Current Protection	Yes, 9.0A circuit breaker
Suppression Joule Rating	680
Surge Test Conditions	Per ANSI/IEEE C62.41 - IEEE587 Cat. A & B test waveforms
Total Harmonic Distortion	less than 1%
VA / Watt Capacity	1000
Transformer Type	Low impedance transformer-based line isolation transformer
OUTPUT	
Output Receptacles	(4) 5-15R
Output Amp Capacity	8.3
INPUT	
Input Cord Length (ft.)	6
Input Cord Length (m)	1.83
Input Plug Type	NEMA 5-15P
SURGE / NOISE SUPPRESSION	
Noise Suppression Rating	33-65dB normal mode; >80dB common mode
PHYSICAL	
Shipping Dimensions (hwd / in.)	6.25 x 13 x 7.5
Shipping Dimensions (hwd / cm)	15.88 x 33 x 19.1
Shipping Weight (lbs.)	24.6
Shipping Weight (kg)	11.15



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Unit Dimensions (hwd / in.)	5.5 x 6.25 x 8.5
Unit Dimensions (hwd / cm)	13.97 x 15.88 x 21.6
Unit Weight (lbs.)	22.6
Unit Weight (kg)	10.25
Cooling Method	Convection
Form Factors Supported	Tower
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>