



T1M74-L-01-F

IPM1-08-D

MMTD-06-20-F-03.25-D-TUS

(2.54 mm) .100"

MMTD, MMTDT, MMTS, MMTST, IPM1, T1M74-L, T1M74-R SERIES

DISCRETE WIRE COMPONENTS & TOOLING

Mates with:
MMSD(T), MMSS(T)
-TXS Mates with:
IPL1

SPECIFICATIONS

For complete specifications see
www.samtec.com?MMTD,
www.samtec.com?MMTDT,
www.samtec.com?MMTS or
www.samtec.com?MMTST

Insulator Material:

Nylon, White

Contact Material:

Phosphor Bronze

Wire:

20 to 30 AWG

Plating:

Au over 50 μ" (1.27 μm) Ni

Operating Temp Range:

-10 °C to +105 °C (20-26 AWG)

-10 °C to +80 °C (28-30 AWG)

-40 °C to +125 °C

(*Teflon™ Fluoropolymer)

Voltage Rating:

600 VAC

RoHS Compliant:

Yes

*Teflon™ is a trademark of
The Chemours Company FC,
LLC used under license by
Samtec.

RECOGNITIONS

For complete scope
of recognitions see
www.samtec.com/quality



FILE NO. ET11594

TYPE	PINS PER ROW	WIRE GAUGE	PLATING OPTION	ASSEMBLY LENGTH	END OPTION	OPTION
MMTD = Double Row PVC Cable	-02, -03, -04, -05, -06, -08, -10, -12, -15, -16, -20, -25 (Standard sizes)	-20 -20C = Color Coded Cable (MMTD & MMTS only)	-F = Gold flash on contact -L = 10 μ" (0.25 μm) Gold on contact	- "XX.XX" = Assembly Length in Inches -S= (76.2 mm) 03.00" min. -D= (82.6 mm) 03.25" min.	-S = Single End -D = Double End	(Only available with -D) -TUS = Socket on End 2, latch up -TDS = Socket on End 2, latch down
MMTDT = Double Row Blue *Teflon™ Fluoropolymer Cable (20, 24, 28 & 30 Wire Gauge only)		-22 -24 -24C = Color Coded Cable (MMTD & MMTS only)				
MMTS = Single Row PVC Cable		-26 -28 -28C = Color Coded Cable (MMTD & MMTS only)				
MMTST = Single Row Blue *Teflon™ Fluoropolymer Cable (20, 24, 28 & 30 Wire Gauge only)		-30				

Note:
Some lengths, styles and options are non-standard, non-returnable.

Diagram labels: MMTD(T), MMTS(T), dimensions: (7.62) .300, (8.89) .350, (5.08) .200, (7.62) .300, (17.53) .690, (2.54) .100, (2.54) .100, (1.78) .070, No. of positions x (2.54) .100, 01, 10, 11, (2.54) .100, (2.54) .100.

APPLICATION

-20C, -24C, -28C
CABLE
COLOR CODING
(PVC CABLE ONLY)

PIN	COLOR
1	BROWN
2	RED
3	ORANGE
4	YELLOW
5	GREEN
6	BLUE
7	VIOLET
8	GRAY
9	WHITE
10	BLACK
ETC	REPEAT

SPECIFICATIONS

For complete specifications see
www.samtec.com?IPM1,
www.samtec.com?T1M74-L or
www.samtec.com?T1M74-R

TOOLING

- Hand Tool:
CAT-HT-174-2030-13
- Mini Applicator (20-24 AWG):
CAT-MC-174-2024-XX-01
- Mini Applicator (26-30 AWG):
CAT-MC-174-2630-XX-01
- Extraction Tool:
CAT-EX-74-01

TYPE	POSITIONS PER ROW	ROW OPTION	TYPE	WIRE GAUGE	PLATING OPTION
IPM1 = Body, Loose	-02, -03, -04, -05, -06, -08, -10, -12, -15, -16, -20, -25 (Standard sizes)	-S = Single Row -D = Double Row	T1M74-L = Contact, Loose T1M74-R = Contact, Full Reel (15,300 Parts per Reel)	-01 = 26 to 30 AWG -02 = 20 to 24 AWG	-F = Gold flash on contact -L = 10 μ" (0.25 μm) Gold on contact

Diagram labels: IPM1, T1M74-L, T1M74-R, dimensions: (7.62) .300, (5.08) .200, (17.53) .690, (19.33) .761, (1.57) .062 DIA, (3.81) .150, (1.91) .075, (3.17) .125.