

Product data sheet

Specifications

APC IT Power Distribution Module 3 Pole 5 Wire 40A IEC 309 500cm



PDM3540IEC309-500

Overview

Presentation Factory assembled and tested Power Distribution Modules include circuit breaker, power cord, power connection, and circuit monitoring. Auto-detection of modules by the Modular PDU minimizes installation time.

Lead time Usually Ships within 3 Weeks

Main

Main Input Voltage 415 V 3 phases

Main Output Voltage 240 V

Provided equipment Installation guide

Physical

Colour Grey

Height 12.7 cm

Width 44.4 cm

Depth 40.6 cm

Net weight 6.27 kg

Input

Network frequency 60 Hz

Permissible voltage 200...240 V

Max line current 40 A

Output

Max current draw 40 A

Number of power socket outlets 1 IEC 309

Conformance

Product certifications UL listed

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 12.7 cm

Package 1 Width 40.6 cm

Package 1 Length	44.4 cm
------------------	---------

Package 1 Weight	6.82 kg
------------------	---------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Take-back Transparency

Resource performance

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Under investigation

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)