

	PLUG: RECEPTACLE: RECEPTACLE	WB40PR8 WB40SD6 XXXXXXXXXXXX			
PLUG	,				
	SERIES				
WB 2 row, right angle, plug, with mounting ears	WB 2 row, straight, receptacle, with mounting ears				
SIZE					
20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 128, 132	20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 128, 132				
	CONTACTS				
TYPE CONTACTS/TERMINATIONS: PR8 Pin, right angle, dip solder, .125"	TYPE CONTACTS/TERMINATIONS: SD6 Socket, straight, dip solder, .095" SD9 Socket, straight, dip solder, .140" SD12 Socket, straight, dip solder, .190" SD19 Socket, straight, dip solder, .300"				
	HARDWARE				
STYLE OF HARDWARE: (See WB-9)K*_*Integral keying guides, polarizedKY*_*Stainless steel keying guides, polarizedJMM2 stainless steel fixed jackscrews	STYLE OF HARDWARE: (See WB-9)K*_*Integral keying guides, polarizedKY*_*Stainless steel keying guides, polarizedJTFF2 stainless steel turning jacksockets				

DIMENSIONS						
SIZE	А	В	С	D	Е	
20	1.150	.900	.450	1.030	.750	
30	1.400	1.150	.700	1.280	1.000	
40	1.650	1.400	.950	1.530	1.250	
50	1.900	1.650	1.200	1.780	1.500	
60	2.150	1.900	1.450	2.030	1.750	
70	2.400	2.150	1.700	2.280	2.000	
80	2.650	2.400	1.950	2.530	2.250	
90	2.900	2.650	2.200	2.780	2.500	
100	3.150	2.900	2.450	3.030	2.750	
110	3.400	3.150	2.700	3.280	3.000	
128	3.850	3.600	3.150	3.730	3.450	
132	3.950	3.700	3.250	3.830	3.550	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AirBorn:

WB60SD9 WB90SD9JTFF WB100SD9JTFF WB110PR8JMM WB60SD9JTFF WB40SD9JTFF WB30PR8 WB128PR8 WB60PR8JMM WB60PR8 WB110SD9JTFF WB50SD9 WB100PR8JMM WB132SD9JTFF WB70PR8JMM WB80PR8 WB50SD9JTFF WB70SD9JTFF WB132PR8JMM WB30PR8JMM WB132SD9 WB80SD9 WB20SD9JTFF WB50PR8 WB100SD9 WB90PR8 WB40PR8JMM WB90SD9 WB80PR8JMM WB20PR8JMM WB128SD9JTFF WB40SD9 WB100PR8 WB100PR8 WB30SD9JTFF WB40PR8 WB70PR8 WB132PR8 WB128SD9 WB110SD9 WB128PR8JMM WB50PR8JMM WB70SD9 WB20SD9 WB80SD9JTFF WB30SD9 WB90PR8JMM WB20PR8