

[Custom Capabilities](#)[Test Accessories](#)[Plugs, Jacks, Posts](#)[Connectors](#)[Hardware](#)[S](#)[Home](#)[About Abbatron](#)[Products](#)[Locate Distributor
or Representative](#)[Contact Us](#)[Request Information](#)[Site Map](#)

Ceramic Spacers

- Ceramic spacers are Grade L-5 Steatite, glazed and fired at high temperature
- Threaded from each end as indicated in table
- Continuous safe operating Temperature Rating of 930°C(1700°F)
- Other size Options are available from factory in quantity, as are spacers with sizes at each end for adaption applications



 Ceramic Spacers drawing

Inventory Search

Cross Reference

UPS Tracking

632 Arch Street, POB 726
Meadville, PA 16335 USA
814-724-6440
Contact Webmaster
© 2006

PART NO.	LENGTH	O.D.	THREAD		MIL NUMBER		
			SIZE	DEPTH			
2640	1/4	1/4	6-32	THRU	NL 523 W01 004		
2642	3/8	3/8		5/32			
2641	1/2	1/4		3/16			
2643		3/8		5/32			
2600		1/2		9/64			
2644	5/8	3/8		8-32		1/4	NL 523 W01 005
2601		1/2		3/16		NL 523 W02 005	
2602	3/4	3/8	6-32	1/4	NL 523 W01 006		
2645		1/2	8-32		NL 523 W02 006		
2608		3/8	6-32		NL 523 W01 008		
2603	1	1/2	8-32	3/8	NL 523 W02 008		
2646		3/4	10-32		NL 523 W03 008		
2609	1-1/4	3/8	6-32	3/8	NL 523 W01 010		
2615		1/2	8-32		NL 523 W02 010		
2604		3/4	10-32		NL 523 W03 010		
2610		1	1/4-20		7/16	NL 523 W04 010	
2616	1-1/2	1/2	6-32	3/8	NL 523 W01 012		
2647		3/8	8-32				
2605		1/2	10-32				
2611		3/4	1/4-20			1/2	NL 523 W04 012
2617	2	1	6-32	3/8	NL 523 W01 016		
2623		1/2	8-32		NL 523 W02 016		
2606		3/4	10-32		NL 523 W03 016		
2612		1	1/4-20		5/8	NL 523 W04 016	
2618	2-1/2	1/2	6-32	3/8	NL 523 W02 020		
2648		1/2	8-32				
2613		3/4	10-32			NL 523 W03 020	
2619		1	1/4-20			3/4	
2649	3	1	5/8	3/8	NL 523 W04 020		
2625		1/2	8-32		NL 523 W02 024		
2614		3/4	10-32		NL 523 W03 024		
2620		1	1/4-20		5/8	NL 523 W04 024	
2626	4	3/4	10-32	3/8	NL 523 W03 032		
2650		1	3/4				
2621	5	1	1/4-20	5/8	NL 523 W04 032		
2627		1	5/8		NL 523 W04 040		
2628		1	5/8		NL 523 W04 048		
2629	6	1	1/4-20	5/8	NL 523 W04 048		

Maximum Thread Depth					
Thread Size	2 - 56	4 - 40	6 - 32	8 - 32	10 - 32
Thread Length Tapped Thru	0.375	0.500	1.000	1.000	1.000
Thread Length Tap each end	0.250	0.375	0.375	0.375	0.375

[home](#) | [about abbatron](#) | [products](#) | [locate distributor or representative](#) | [contact us](#) | [request information](#) | [site map](#)