





Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating


Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0.1 mm
Coplanarity Area of Termination ≤ 0.1 mm

Verpackt in Gurtverpackung
Tape on Reel Packaging
Verpackungseinheit: 440 Stück
Packaging unit: 440 pcs



Abspulrichtung - Reel off Direction



454193		weiß white	0.3	4.5	0.9	3.9	Codierung wie Variante schwarz Encoding such variant black
384474		rot red	3.9	0.9	4.5	0.3	
384473		grün green	2.7	2.1	3.3	1.5	
384472		blau blue	1.5	3.3	2.1	2.7	
384471		schwarz black	0.3	4.5	0.9	3.9	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Information:	Tolerances		Scale	3:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation
		www.ERNI.com		M 2.54 SRC-A, 4-polig
b	15.04.2013	324068		I
Index	Date	Class		A2
				SRCA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[384472](#)