2057404-1 ACTIVE

IMPACT

TE Internal #: 2057404-1

60 Position, Mating Alignment, Guide Slot Mating Alignment Type, 6 Row, 10 Column, PCB Mount Receptacle, IMPACT, High Speed

Backplane Connectors

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Number of Positions: 60

Row-to-Row Spacing: 1.35 mm [.053 in]

Mating Alignment: With

Mating Alignment Type: Guide Slot

Number of Rows: 6

Features

Product Type Features

Signal Arrangement	Differential
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Receptacle
Shroud Style	Unshrouded
Configuration Features	
Number of Ground Positions	20
Number of Pairs	20
Stackable	No
Number of Signal Positions	40
Number of Positions	60
Number of Rows	6
Number of Columns	10
PCB Mount Orientation	Right Angle
Guide Location	Right
Electrical Characteristics	
Impedance	100 Ω

30 VAC

Operating Voltage



Signal Characteristics

Number of Differential Pairs per Column	2
Data Rate	20 – 25 Gb/s

Body Features

Drives and Dreamber of Callana	DII-	
Primary Product Color	Black	

Contact Features

PCB Contact Termination Area Plating Material Thickness	1.27 μm[50 μin]
Contact Layout	Inline
Contact Type	Socket
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	.762 μm[30 μin]
Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Dual Beam
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	.75 A

Termination Features

Termination Post & Tail Length	1.2 mm[.047 in]
Termination Method to PCB	Through Hole - Press-Fit

Mechanical Attachment

PCB Mount Alignment Type	Locating Posts
Guide Hardware	With
Mating Retention	Without
PCB Mount Retention	With
PCB Mount Retention Type	Action/Compliant Tail & Screw
Mating Alignment	With
Mating Alignment Type	Guide Slot
Connector Mounting Type	Board Mount

Housing Features

Number of Shrouded Sides 0	



None
LCP - GF (Liquid Crystal Polymer)
1.9 mm[.075 in]
26.6 mm[1.047 in]
10.9 mm[.429 in]
20.1 mm[.791 in]
1.6 mm
.39 mm[.015 in]
1.35 mm[.053 in]
-55 – 85 °C[-67 – 185 °F]
Signal
Signal
Signal CSA Certified, UL E28476
CSA Certified, UL E28476

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | IMPACT



Customers Also Bought













TE Part #4-1971846-2 2P, RAST 5 Tab Header, THV



TE Part #2180613-1 IMP100,S,H,RA2P10C,LG,OEW39SL TE Part #2232580-2 2P, PL RAST 5 Tab Header,TH, Vertical

TE Part #2232580-5 5P, PL RAST 5 Tab Header, TH,Vertical

TE Part #2271302-1 AMPMODU, PIN, 2.0P, RA, TH, 30P, 3U' AU

TE Part #2110820-6

SFP+assy 2x2 Spring Fingers Inner LP

Documents

Product Drawings

IMP100S,R,RA2P10C,RG,39

English

CAD Files

Customer View Model

ENG_CVM_CVM_2057404-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2057404-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2057404-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

7-1773458-1_IMPACT_BACKPLANE_CONNECTOR_SYSTEM_CATALOG

English

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

60 Position, Mating Alignment, Guide Slot Mating Alignment Type, 6 Row, 10 Column, PCB Mount Receptacle, IMPACT, High Speed Backplane Connectors



English