


SOLISTRAND

TE Internal #: 8-324001-1 Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, 1.09 mm [.043 in] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, Splices

View on TE.com >

Terminals & Splices > Splices



Splice Type: Butt Splice

Wire Size: .2 – .6 mm²

Sealable: No

Splice Features: Serrated

Features

Product Type Features



¥	

Splice Accessory Type	Splice
Splice Type	Butt Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Product Weight	.332 g
Product Weight Splice Features	.332 g Serrated
Splice Features	
Splice Features Contact Features	Serrated
Splice Features Contact Features Terminal Plating Material	Serrated

8-324001-1

Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, 1.09 mm [.043 in] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, Splices



Mechanical Attachment

Wire Insulation Support	Without
Dimensions	
Outside Diameter	2.67 mm[.105 in]
Wire Size	320 – 1290 CMA
Barrel Inside Diameter	1.09 mm[.043 in]
Terminal Material Thickness	.6 mm[.024 in]
Product Length	12.45 mm[.49 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	
Operation/Application Compatible With Wire Base Material	Copper
	Copper
Compatible With Wire Base Material	Copper
Compatible With Wire Base Material Industry Standards	

Packaging Method

Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

8-324001-1

Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, 1.09 mm [.043 in] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, Splices




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



Documents

Product Drawings SPLICE, SOLIS BUTT STRAP 24-20

English

CAD Files

Customer View Model

8-324001-1

Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, 1.09 mm [.043 in] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, Splices



ENG_CVM_8-324001-1_G.3d_igs.zip

English

Customer View Model

ENG_CVM_8-324001-1_G.3d_stp.zip

English

Customer View Model

ENG_CVM_8-324001-1_G.2d_dxf.zip

English

3D PDF

3D

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-324001-1_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-324001-1_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-324001-1_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals



English