

## PennEngineering Corporate Headquarters – Danboro, PA

5190 Old Easton Rd. Danboro, PA 18916 **Phone:** 215-766-8853


**Toll-Free Phone:** 1-800-237-4736 (U.S. only)

**Email:** <a href="mailto:info@pemnet.com">info@pemnet.com</a> **Website:** <a href="mailto:www.pemnet.com">www.pemnet.com</a>

## Part # KF2-632-ET, Broaching Nuts - Types KF2, KFS2 - Unified

**Type KF2 and KFS2** - Broaching nuts, internally threaded for mounting on PC boards.





Specifications		
Thread Size	.138-32 (#6- 32)	
Thread Code	632	
A (Shank) Max.	.060 in	
Min. Sheet Thickness	.060 in	
Hole Size in Sheet + .003000	.213 in	
C ± .003	.231 in	
E ± .005	.281 in	
T ± .005	.065 in	
Min. Dist. Hole C/L to Edge	.22 in	
For Use in Sheet Hardness <sup>1</sup>	HRB 60 / HB 107 or Less	PC Board
Thread Specification	Internal, ASME B1.1, 2B	
Fastener Material	Carbon Steel	
Standard Finish	Electro-Plated Tin, ASTM B545, Class B with Preservative Coating, Annealed	
CAD Supplier	PennEngineering ® (PEM ®)	

<sup>1</sup> HRB - Hardness Rockwell "B" Scale. HB - Hardness Brinell.