

TPS22916xx 1-V – 5.5-V, 2-A, 60-mΩ Ultra-Low Leakage Load Switch

1 Features

- Input Operating Voltage Range (V_{IN}): 1 V–5.5 V
- Maximum Continuous Current (I_{MAX}): 2 A
- ON-Resistance (R_{ON}):
 - 5 V_{IN} = 60 mΩ (typ), 100 mΩ (85°C max)
 - 1.8 V_{IN} = 100 mΩ (typ), 150 mΩ (85°C max)
 - 1 V_{IN} = 200 mΩ (typ), 325 mΩ (85°C max)
- Ultra-Low Power Consumption:
 - ON State (I_Q): 0.5 μA (typ), 1 μA (max)
 - OFF State (I_{SD}): 10 nA (typ), 100 nA (max)
 - TPS22916CL (I_{SD}): 100 nA (typ), 300 nA (max)
- Smart ON Pin Pull Down (R_{PD}):
 - ON $\geq V_{IH}$ (I_{ON}): 10 nA (max)
 - ON $\leq V_{IL}$ (R_{PD}): 750 kΩ (typ)
- Slow Timing in C Version Limits Inrush Current:
 - 5-V Turnon time (t_{ON}): 1400 μs at 5 mV/μs
 - 1.8-V Turnon time (t_{ON}): 3000 μs at 1 mV/μs
 - 1-V Turnon time (t_{ON}): 6500 μs at 0.3 mV/μs
- Fast Timing in B Version Reduces Wait Time:
 - 5-V Turnon time (t_{ON}): 115 μs at 57 mV/μs
 - 1.8-V Turnon time (t_{ON}): 250 μs at 12 mV/μs
 - 1-V Turnon time (t_{ON}): 510 μs at 3.3 mV/μs
- Always-ON True Reverse Current Blocking (RCB):
 - Activation Current (I_{RCB}): –500 mA (typ)
 - Reverse Leakage ($I_{IN,RCB}$): –300 nA (max)
- Quick Output Discharge (QOD): 150 Ω (typ) (N version has no QOD)
- Active Low Enable Option (L Version)

2 Applications

- Wearables
- Smartphones
- Tablets
- Portable Speakers

3 Description

The TPS22916xx is a small, single channel load switch using a low leakage P-Channel MOSFET for minimum power loss. Advanced gate control design supports operating voltages as low as 1 V with minimal increase in ON-Resistance and power loss.

Multiple timing options are available to support various system loading conditions. For heavy capacitive loads, the slow turnon timing in the C version minimizes the inrush current. In cases with light capacitive loads, the fast timing in the B version reduces required wait time.

The switch ON state is controlled by a digital input that is capable of interfacing directly with low-voltage control signals. Both Active High and Active Low (L) versions are available. When power is first applied, a Smart Pull Down is used to keep the ON pin from floating until system sequencing is complete. Once the ON pin is deliberately driven high ($\geq V_{IH}$), the Smart Pull Down is disconnected to prevent unnecessary power loss.

The TPS22916xx is available in a small, space saving 0.78 mm × 0.78 mm, 0.4-mm pitch, 0.5-mm height 4-pin Wafer-Chip-Scale (WCSP) package (YFP). The device is characterized for operation over a temperature range of –40°C to +85°C.

Device Information⁽¹⁾


| PART NUMBER | PACKAGE | BODY SIZE (NOM) |
|-------------|----------|-------------------|
| TPS22916xx | WCSP (4) | 0.78 mm × 0.78 mm |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

Device Comparison Table

| VERSION | TIMING | QOD | ENABLE (ON) |
|------------|--------|-----|-------------|
| TPS22916B | Fast | Yes | Active High |
| TPS22916C | Slow | Yes | Active High |
| TPS22916CN | Slow | No | Active High |
| TPS22916CL | Slow | Yes | Active Low |

Simplified Schematic



Copyright © 2017, Texas Instruments Incorporated



Table of Contents

| | | | |
|--|-----------|--|-----------|
| 1 Features | 1 | 8.4 Device Functional Modes..... | 17 |
| 2 Applications | 1 | 9 Application and Implementation | 18 |
| 3 Description | 1 | 9.1 Application Information..... | 18 |
| 4 Revision History | 2 | 10 Power Supply Recommendations | 19 |
| 5 Pin Configuration and Functions | 3 | 11 Layout | 20 |
| 6 Specifications | 4 | 11.1 Layout Guidelines | 20 |
| 6.1 Absolute Maximum Ratings | 4 | 11.2 Layout Example | 20 |
| 6.2 ESD Ratings..... | 4 | 11.3 Thermal Considerations | 20 |
| 6.3 Recommended Operating Conditions..... | 4 | 12 Device and Documentation Support | 21 |
| 6.4 Thermal Information | 4 | 12.1 Documentation Support | 21 |
| 6.5 Electrical Characteristics..... | 5 | 12.2 Receiving Notification of Documentation Updates | 21 |
| 6.6 Switching Characteristics | 6 | 12.3 Community Resources..... | 21 |
| 6.7 Typical Characteristics | 8 | 12.4 Trademarks | 21 |
| 7 Parameter Measurement Information | 15 | 12.5 Electrostatic Discharge Caution..... | 21 |
| 8 Detailed Description | 16 | 12.6 Glossary | 21 |
| 8.1 Overview | 16 | 13 Mechanical, Packaging, and Orderable | 21 |
| 8.2 Functional Block Diagram | 16 | Information | 21 |
| 8.3 Feature Description..... | 16 | 13.1 Package Option Addendum | 22 |

4 Revision History


| Changes from Revision C (October 2018) to Revision D | Page |
|---|-------------|
| • Changed package dimensions from 0.74 mm x 0.74 mm to 0.78 mm x 0.78 mm..... | 1 |

| Changes from Revision B (December 2017) to Revision C | Page |
|--|-------------|
| • Changed Package Drawing Dimensions | 21 |

| Changes from Revision A (September 2017) to Revision B | Page |
|---|-------------|
| • Changed Pinout drawing labeled Laser Marking..... | 1 |

| Changes from Original (July 2017) to Revision A | Page |
|---|-------------|
| • Changed device document from Advanced Info to Production Data | 1 |

5 Pin Configuration and Functions



TPS22916xx Pin Functions

| PIN | | TYPE | DESCRIPTION |
|-----|------|---------------|---------------|
| NO. | NAME | | |
| A1 | VOUT | Power | Switch output |
| A2 | VIN | Power | Switch input |
| B1 | GND | Ground | Device ground |
| B2 | ON | Digital input | Device enable |

6 Specifications

6.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)⁽¹⁾

| | | MIN | MAX | UNIT |
|--------------------|--|------|-----|------|
| V _{IN} | Input voltage | -0.3 | 6 | V |
| V _{OUT} | Output voltage | -0.3 | 6 | V |
| V _{ON} | Enable voltage | -0.3 | 6 | V |
| I _{MAX} | Maximum continuous switch current | | 2 | A |
| I _{PLS} | Maximum pulsed switch current, pulse < 300-μs, 2% duty cycle | | 2.5 | A |
| T _{J,MAX} | Maximum junction temperature | | 125 | °C |
| T _{STG} | Storage temperature | -65 | 150 | °C |
| T _{LEAD} | Maximum Lead temperature (10-s soldering time) | | 300 | °C |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

6.2 ESD Ratings

| | | VALUE | UNIT |
|--------------------|-------------------------|--|------|
| V _(ESD) | Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾ | V |
| | | Charged-device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾ | |
| | | ±2000 | |
| | | ±500 | |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 500-V HBM is possible with the necessary precautions. Pins listed as ±2000 V may actually have higher performance.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 250-V CDM is possible with the necessary precautions. Pins listed as ±500 V may actually have higher performance.

6.3 Recommended Operating Conditions

Over operating free-air temperature range (unless otherwise noted)

| | | MIN | MAX | UNIT |
|------------------|--------------------------------|-----|------|------|
| V _{IN} | Input voltage | 1 | 5.5 | V |
| V _{OUT} | Output voltage | 0 | 5.5 | V |
| V _{IH} | High-level input voltage, ON | 1 | 5.5 | V |
| V _{IL} | Low-level input voltage, ON | 0 | 0.35 | V |
| T _A | Operating free-air temperature | -40 | 85 | °C |

6.4 Thermal Information

| Thermal Parameters ⁽¹⁾ | TPS22916xx | UNIT | |
|-----------------------------------|--|------|------|
| | YFP (WCSP) | | |
| | 4 PINS | | |
| θ _{JA} | Junction-to-ambient thermal resistance | 193 | °C/W |
| θ _{JCtop} | Junction-to-case (top) thermal resistance | 2.3 | °C/W |
| θ _{JB} | Junction-to-board thermal resistance | 36 | °C/W |
| ψ _{JT} | Junction-to-top characterization parameter | 12 | °C/W |
| ψ _{JB} | Junction-to-board characterization parameter | 36 | °C/W |

- (1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

6.5 Electrical Characteristics

Unless otherwise noted, the specification in the following table applies for all variants over the entire recommended power supply voltage range of 1 V to 5.5 V unless noted otherwise. Typical Values are at 25°C.

| PARAMETER | | TEST CONDITIONS | T _J | MIN | TYP | MAX | UNIT |
|---------------------------------------|-----------------------------------|---|-------------------------|-----------------|-----|-----|------|
| INPUT SUPPLY (VIN) | | | | | | | |
| I _{Q,VIN} | V _{IN} Quiescent current | Enabled, V _{OUT} = Open | –40°C to +85°C | 0.5 | 1.0 | | μA |
| I _{SD,VIN} | V _{IN} Shutdown current | Disabled, V _{OUT} = GND (TPS22916B/C/CN) | –40°C to +85°C | 10 | 100 | | nA |
| | | Disabled, V _{OUT} = GND (TPS22916CL) | –40°C to +85°C | 100 | 300 | | nA |
| ON-RESISTANCE (R_{ON}) | | | | | | | |
| R _{ON} | ON-Resistance | I _{OUT} = 200 mA | V _{IN} = 5 V | 25°C | 60 | 80 | mΩ |
| | | | | –40°C to +85°C | | 100 | |
| | | | | –40°C to +105°C | | 120 | |
| | | | V _{IN} = 3.6 V | 25°C | 70 | 90 | |
| | | | | –40°C to +85°C | | 120 | |
| | | | | –40°C to +105°C | | 140 | |
| | | | V _{IN} = 1.8 V | 25°C | 100 | 125 | |
| | | | | –40°C to +85°C | | 150 | |
| | | | | –40°C to +105°C | | 175 | |
| | | | V _{IN} = 1.2 V | 25°C | 150 | 200 | |
| | | | | –40°C to +85°C | | 250 | |
| | | | | –40°C to +105°C | | 300 | |
| | | | V _{IN} = 1 V | 25°C | 200 | 275 | |
| | | | | –40°C to +85°C | | 325 | |
| | | | | –40°C to +105°C | | 375 | |
| ENABLE PIN (ON) | | | | | | | |
| I _{ON} | ON Pin leakage | Enabled | –40°C to +85°C | –10 | | 10 | nA |
| R _{PD} | Smart Pull Down Resistance | Disabled | –40°C to +85°C | | 750 | | kΩ |
| REVERSE CURRENT BLOCKING (RCB) | | | | | | | |
| I _{RCB} | RCB Activation Current | Enabled, V _{OUT} > V _{IN} | –40°C to +85°C | –500 | | | mA |
| t _{RCB} | RCB Activation time | Enabled, V _{OUT} > V _{IN} + 200mV | –40°C to +85°C | | 10 | | μs |
| V _{RCB} | RCB Release Voltage | Enabled, V _{OUT} > V _{IN} | –40°C to +85°C | | 25 | | mV |
| I _{IN,RCB} | VIN Reverse Leakage Current | 0 V ≤ V _{IN} + V _{RCB} ≤ V _{OUT} ≤ 5.5 V | –40°C to +85°C | –300 | | | nA |
| QUICK OUTPUT DISCHARGE (QOD) | | | | | | | |
| QOD ⁽¹⁾ | Output discharge resistance | Disabled (Not in TPS22916CN) | –40°C to +85°C | | 150 | | Ω |

(1) For more information on which devices include quick output discharge, see the [Device Functional Modes](#) section.

6.6 Switching Characteristics

Unless otherwise noted, the typical characteristics in the following table applies over the entire recommended power supply voltage range of 1 V to 5.5 V at 25°C with a load of $C_L = 0.1\mu\text{F}$, $R_L = 10\Omega$.

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-------------------------|---------------|--|-----|-----|-----|-------------------------|
| TPS22916B | | | | | | |
| t_{ON} | Turn On Time | $V_{\text{IN}} = 5\text{ V}$ | | 115 | | μs |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 140 | | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 250 | | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 350 | | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 510 | | |
| t_{RISE} | Rise Time | $V_{\text{IN}} = 5\text{ V}$ | | 70 | | μs |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 80 | | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 130 | | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 190 | | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 240 | | |
| SR_{ON} | Slew Rate | $V_{\text{IN}} = 5\text{ V}$ | | 57 | | $\text{mV}/\mu\text{s}$ |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 36 | | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 12 | | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 5.1 | | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 3.3 | | |
| t_{OFF} | Turn Off Time | $V_{\text{IN}} = 5\text{ V}$ | | 5 | | μs |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 5 | | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 10 | | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 15 | | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 25 | | |
| t_{FALL} | Fall Time | $C_L = 0.1\mu\text{F}$, $R_L = 10\Omega^{(1)}$ | | 2.3 | | μs |
| | | $C_L = 1\mu\text{F}$, $R_L = \text{Open}^{(1)}$ | | 315 | | |

(1) See the [Fall Time \(\$t_{\text{FALL}}\$ \) and Quick Output Discharge \(QOD\)](#) section for information on how R_L and C_L affect Fall Time.

Switching Characteristics (continued)

Unless otherwise noted, the typical characteristics in the following table applies over the entire recommended power supply voltage range of 1 V to 5.5 V at 25°C with a load of $C_L = 0.1\mu\text{F}$, $R_L = 10\Omega$.


| PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|--------------------------|--|-----|------|-------------------------|
| TPS22916C, TPS22916CN, TPS22916CL | | | | | |
| t_{ON} | Turn On Time | $V_{\text{IN}} = 5\text{ V}$ | | 1400 | μs |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 1700 | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 3000 | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 5000 | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 6500 | |
| t_{RISE} | Rise Time | $V_{\text{IN}} = 5\text{ V}$ | | 800 | μs |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 900 | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 1400 | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 2300 | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 3000 | |
| SR_{ON} | Slew Rate | $V_{\text{IN}} = 5\text{ V}$ | | 5 | $\text{mV}/\mu\text{s}$ |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 3.2 | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 1 | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 0.4 | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 0.3 | |
| t_{OFF} | Turn Off Time | $V_{\text{IN}} = 5\text{ V}$ | | 5 | μs |
| | | $V_{\text{IN}} = 3.6\text{ V}$ | | 5 | |
| | | $V_{\text{IN}} = 1.8\text{ V}$ | | 10 | |
| | | $V_{\text{IN}} = 1.2\text{ V}$ | | 15 | |
| | | $V_{\text{IN}} = 1\text{ V}$ | | 25 | |
| t_{FALL} | Fall Time ⁽²⁾ | $C_L = 0.1\mu\text{F}$, $R_L = 10\Omega$ ⁽¹⁾ | | 2.3 | μs |
| | | $C_L = 10\mu\text{F}$, $R_L = \text{Open}$ ⁽¹⁾ | | 3150 | |

(2) Devices without Quick Output Discharge (QOD) may not discharge completely.


6.7 Typical Characteristics

6.7.1 Typical Electrical Characteristics


The typical characteristics curves in this section apply to all devices unless otherwise noted.




Enabled
Figure 1. ON-Resistance vs Temperature




Enabled
Figure 2. ON-Resistance vs Input voltage




TPS22916C, TPS22916CN, TPS22916B $V_{ON} \leq V_{IL}$
Figure 3. Shutdown Current



TPS22916CL $V_{ON} \geq V_{IH}$
Figure 4. Shutdown Current (Active Low)





Enabled
Figure 5. Quiescent Current



-40°C to +85°C

Figure 6. ON Pin Threshold

Typical Electrical Characteristics (continued)



6.7.2 Typical Switching Characteristics

The typical data in this section apply to all devices at 25°C unless otherwise noted.




Figure 9. Fast Turn On Time




Figure 10. Fast Turn On at 5 V




Figure 11. Fast Rise Time




Figure 12. Fast Turn On at 3.6 V




Figure 13. Fast Slew Rate




Figure 14. Fast Turn on at 1 V

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.




Figure 15. Fast Turn On vs Load Capacitance




Figure 16. Fast Turn On vs Load Resistance




Figure 17. Fast Rise Time vs Load Capacitance




Figure 18. Fast Rise Time vs Load Resistance




Figure 19. Fast Slew Rate vs Load Capacitance




Figure 20. Fast Slew Rate vs Load Resistance

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.




Figure 21. Slow Turn on Time




Figure 22. Slow Turn on at 5 V




Figure 23. Slow Rise Time




Figure 24. Slow Turn On at 3.6 V




Figure 25. Slow Slew Rate




Figure 26. Slow Turn On at 1 V

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.




Figure 27. Slow Turn On vs Load Capacitance




Figure 28. Slow Turn On vs Load Resistance




Figure 29. Slow Rise Time vs Load Capacitance




Figure 30. Slow Rise Time vs Load Resistance




Figure 31. Slow Slew Rate vs Load Capacitance




Figure 32. Slow Slew Rate vs Load Resistance

Typical Switching Characteristics (continued)

The typical data in this section apply to all devices at 25°C unless otherwise noted.




Figure 33. Turn Off Time




Figure 34. Turn Off at 5 V (Active Low)




Figure 35. Fall Time

7 Parameter Measurement Information




Figure 36. TPS22916 Test Circuit




Figure 37. TPS22916 Timing Waveform


8 Detailed Description

8.1 Overview

This family of devices are single channel, 2-A load switches in ultra-small, space saving 4-pin WCSP package. These devices implement a low resistance P-channel MOSFET with a controlled rise time for applications that need to limit inrush current.

These devices are designed to have very low leakage current during off state. This prevents downstream circuits from pulling high standby current from the supply. Integrated control logic, driver, power supply, and output discharge FET eliminates the need for additional external components, which reduces solution size and BOM count.

8.2 Functional Block Diagram



8.3 Feature Description

8.3.1 On and Off Control

The ON pin controls the state of the switch. The ON pin is compatible with standard GPIO logic threshold. It can be used with any microcontroller with 1.2-V, 1.8-V, 2.5-V, 3.3-V, or 5.5-V GPIO.

8.3.2 Fall Time (t_{FALL}) and Quick Output Discharge (QOD)

The TPS22916B/C/CL include a Quick Output Discharge feature. When the switch is disabled, a discharge resistor is connected between VOUT and GND. This resistor has a typical value of QOD and prevents the output from floating while the switch is disabled.

As load capacitance and load resistance increase: t_{FALL} increases. The larger the load resistance or load capacitance is, the longer it takes to discharge the capacitor, resulting in a longer fall time.

Feature Description (continued)

The output fall time is determined by how quickly the load capacitance is discharged and can be found using Equation 1 .

$$t_{\text{FALL}} = - (R_{\text{DIS}}) \times C_L \times \ln(V_{10\%}/V_{90\%})$$

Where

- $V_{10\%}$ is 10% of the initial output voltage
 - $V_{90\%}$ is 90% of the initial output voltage
 - R_{DIS} is the result of the QOD resistance in parallel with the Load Resistance R_L
 - C_L is the load capacitance
- (1)

With the Quick Output Discharge feature, the QOD resistance is in parallel with R_L . This provides a lower total load resistance as seen from the load capacitance which discharges the capacitance faster resulting in a smaller t_{FALL} .

8.3.3 Full-Time Reverse Current Blocking

In a scenario where the device is enabled and V_{OUT} is greater than V_{IN} there is potential for reverse current to flow through the pass FET or the body diode. When the reverse current threshold (I_{RCB}) is exceeded, the switch is disabled within t_{RCB} . The Switch will remain off and block reverse current as long as the reverse voltage condition exists. Once V_{OUT} has dropped below the V_{RCB} release threshold the TPS22916xx will turn back on with slew rate control.

8.4 Device Functional Modes

Table 1 describes the state for each variant as determined by the ON pin

Table 1. Device Function Table

| ON | TPS22916B | TPS22916C | TPS22916CN | TPS22916CL |
|----------------------|-----------|-----------|------------|------------|
| $\leq V_{\text{IL}}$ | Disabled | Disabled | Disabled | Enabled |
| $\geq V_{\text{IH}}$ | Enabled | Enabled | Enabled | Disabled |

Table 2 shows when QOD is active for each variant.

Table 2. QOD Function Table

| Device | TPS22916B | TPS22916C | TPS22916CN | TPS22916CL |
|----------|-----------|-----------|------------|------------|
| Enabled | No | No | No | No |
| Disabled | Yes | Yes | No | Yes |

Table 3 shows when the ON Pin Smart Pull Down is active.

Table 3. Smart-ON Pull Down

| V_{ON} | Pull Down |
|----------------------|--------------|
| $\leq V_{\text{IL}}$ | Connected |
| $\geq V_{\text{IH}}$ | Disconnected |

9 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

9.1 Application Information

This section highlights some of the design considerations when implementing this device in various applications. A PSPICE model for this device is also available in the product page of this device.

9.1.1 Typical Application




Figure 38. Typical Application

9.1.1.1 Design Requirements

For this design example, below, use the input parameters shown in [Table 4](#).

Table 4. Design Parameters

| Design Parameter | Example Value |
|---------------------------------------|---------------|
| Input Voltage (V_{IN}) | 3.6 V |
| Load Capacitance (C_L) | 47 μ F |
| Maximum Inrush Current (I_{RUSH}) | 300 mA |

9.1.1.2 Detailed Design Procedure

9.1.1.2.1 Maximum Inrush Current

When the switch is enabled, the output capacitors must be charged up from 0-V to V_{IN} voltage. This charge arrives in the form of inrush current. Inrush current can be calculated using the following equation:


$$I_{RUSH} = C_L \times SR_{ON} \quad (2)$$

$$I_{RUSH} = 47\mu\text{F} \times 3.2\text{mV}/\mu\text{s} \quad (3)$$

$$I_{RUSH} = 150\text{mA} \quad (4)$$

The TPS22916x offers multiple rise time options to control the inrush current during turn-on. The appropriate device can be selected based upon the maximum acceptable slew rate which can be calculated using the design requirements and the inrush current equation. In this case, the TPS22916C provides a slew rate slow enough to limit the inrush current to the desired amount.

9.1.1.3 Application Curve



$V_{IN} = 3.6\text{ V}$ $C_L = 47\mu\text{F}$ $R_L = \text{Open}$
 TPS22916C $T_A = 25^\circ\text{C}$

Figure 39. Inrush Current

10 Power Supply Recommendations

The device is designed to operate with a V_{IN} range of 1 V to 5.5 V. The V_{IN} power supply must be well regulated and placed as close to the device terminal as possible. The power supply must be able to withstand all transient load current steps. In most situations, using an input capacitance (C_{IN}) of 1 μF is sufficient to prevent the supply voltage from dipping when the switch is turned on. In cases where the power supply is slow to respond to a large transient current or large load current step, additional bulk capacitance may be required on the input.

11 Layout

11.1 Layout Guidelines

For best performance, all traces must be as short as possible. To be most effective, the input and output capacitors must be placed close to the device to minimize the effects that parasitic trace inductances may have on normal operation. Using wide traces for VIN, VOUT, and GND helps minimize the parasitic electrical effects.

11.2 Layout Example

Equation 3 shows an example for these devices. Notice the connection to system ground between the V_{OUT} Bypass Capacitor ground and the GND pin of the load switch, this creates a ground barrier which helps to reduce the ground noise seen by the device.




Figure 40. TPS22916xx Layout

11.3 Thermal Considerations

The maximum IC junction temperature must be restricted to 125°C under normal operating conditions. To calculate the maximum allowable dissipation, P_{D(max)} for a given output current and ambient temperature, use Equation 5 as a guideline:

$$P_{D(\text{MAX})} = \frac{T_{J(\text{MAX})} - T_A}{R_{\theta JA}} \quad (5)$$

Where,

P_{D(max)} = maximum allowable power dissipation

T_{J(max)} = maximum allowable junction temperature

T_A = ambient temperature for the device

θ_{JA} = junction to air thermal impedance. See the [Thermal Information](#) section.

12 Device and Documentation Support

12.1 Documentation Support

12.1.1 Related Documentation

For related documentation see the following:

[TPS22916 Load Switch Evaluation Module](#)

12.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](#). In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

12.3 Community Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

12.4 Trademarks

E2E is a trademark of Texas Instruments.

All other trademarks are the property of their respective owners.

12.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

12.6 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

13 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

13.1 Package Option Addendum

13.1.1 Packaging Information

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/Ball Finish ⁽³⁾ | MSL Peak Temp ⁽⁴⁾ | Op Temp (°C) | Device Marking ⁽⁵⁾⁽⁶⁾ |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|---------------------------------|------------------------------|--------------|----------------------------------|
| TPS22916BYFPR | Active | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | BA |
| TPS22916BYFPT | Active | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | BA |
| TPS22916CLYFPR | Active | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | Call TI | Level-1-260C-UNLIM | -40 to 85 | B9 |
| TPS22916CLYFPT | Active | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | Call TI | Level-1-260C-UNLIM | -40 to 85 | B9 |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PRE_PROD Unannounced device, not in production, not available for mass market, nor on the web, samples not available.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

(4) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(5) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device

(6) Multiple Device markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.


Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


Package Option Addendum (continued)

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/Ball Finish ⁽³⁾ | MSL Peak Temp ⁽⁴⁾ | Op Temp (°C) | Device Marking ⁽⁵⁾⁽⁶⁾ |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|---------------------------------|------------------------------|--------------|----------------------------------|
| TPS22916CNYFPR | Active | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B8 |
| TPS22916CNYFPT | Active | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B8 |
| TPS22916CYFPR | Active | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B7 |
| TPS22916CYFPT | Active | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B7 |


13.1.2 Tape and Reel Information



QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TPS22916BYFPR | DSBGA | YFP | 4 | 3000 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916BYFPT | DSBGA | YFP | 4 | 250 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916CLYFPR | DSBGA | YFP | 4 | 3000 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916CLYFPT | DSBGA | YFP | 4 | 250 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916CNYFPR | DSBGA | YFP | 4 | 3000 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916CNYFPT | DSBGA | YFP | 4 | 250 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916CYFPR | DSBGA | YFP | 4 | 3000 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |
| TPS22916CYFPT | DSBGA | YFP | 4 | 250 | 180.0 | 8.4 | 0.86 | 0.86 | 0.59 | 4.0 | 8.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS


| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TPS22916BYFPR | DSBGA | YFP | 4 | 3000 | 182.0 | 182.0 | 20.0 |
| TPS22916BYFPT | DSBGA | YFP | 4 | 250 | 182.0 | 182.0 | 20.0 |
| TPS22916CLYFPR | DSBGA | YFP | 4 | 3000 | 182.0 | 182.0 | 20.0 |
| TPS22916CLYFPT | DSBGA | YFP | 4 | 250 | 182.0 | 182.0 | 20.0 |
| TPS22916CNYFPR | DSBGA | YFP | 4 | 3000 | 182.0 | 182.0 | 20.0 |
| TPS22916CNYFPT | DSBGA | YFP | 4 | 250 | 182.0 | 182.0 | 20.0 |
| TPS22916CYFPR | DSBGA | YFP | 4 | 3000 | 182.0 | 182.0 | 20.0 |
| TPS22916CYFPT | DSBGA | YFP | 4 | 250 | 182.0 | 182.0 | 20.0 |




PACKAGE OUTLINE

YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.

EXAMPLE BOARD LAYOUT

YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



NOTES: (continued)


- Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SNVA009 (www.ti.com/lit/snva009).

EXAMPLE STENCIL DESIGN

YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



NOTES: (continued)

- 4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|-----------------|------|-------------|-------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| TPS22916BYFPR | ACTIVE | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | BA | Samples |
| TPS22916BYFPT | ACTIVE | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | BA | Samples |
| TPS22916CLYFPR | ACTIVE | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B9 | Samples |
| TPS22916CLYFPT | ACTIVE | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B9 | Samples |
| TPS22916CNYFPR | ACTIVE | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B8 | Samples |
| TPS22916CNYFPT | ACTIVE | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B8 | Samples |
| TPS22916CYFPR | ACTIVE | DSBGA | YFP | 4 | 3000 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B7 | Samples |
| TPS22916CYFPT | ACTIVE | DSBGA | YFP | 4 | 250 | Green (RoHS & no Sb/Br) | SAC396 | Level-1-260C-UNLIM | -40 to 85 | B7 | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=100ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.




(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

⁽⁵⁾ Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

⁽⁶⁾ Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.



4223507/A 01/2017

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.

EXAMPLE BOARD LAYOUT


YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:50X



SOLDER MASK DETAILS
NOT TO SCALE

4223507/A 01/2017

NOTES: (continued)


- Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SNVA009 (www.ti.com/lit/snva009).

EXAMPLE STENCIL DESIGN

YFP0004

DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY



SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:50X

4223507/A 01/2017

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2019, Texas Instruments Incorporated