



Part Number : [475530001](#)

Product Description : 1.27mm Pitch SIM Card Holder with 2 Detect Pins, 6 Circuits, Push-Push Style, Housing Height 1.80mm, without Pegs, Lead-Free

Series Number : 47553

Status : Active

Product Category : Memory / SIM Card Connectors

---

## Documents & Resources

### Drawings

[Drawing 475530001\\_sd.pdf](#)

[Packaging Design Drawing PK-47553-001-001.pdf](#)

### 3D Models and Design Files

[3D Model 475530001\\_stp.zip](#)


### Specifications

[Product Specification PS-47553-001-001.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Memory / SIM Card Connectors
Series	47553
Description	1.27mm Pitch SIM Card Holder with 2 Detect Pins, 6 Circuits, Push-Push Style, Housing Height 1.80mm, without Pegs, Lead-Free
Comments	Without Pegs
Product Family	SD and SIM Memory Card Sockets
Product Name	mini-SIM
Style	Push-Push
UPC	822350925761

### Electrical

Current - Maximum per Contact	0.5A
Shielded	Yes
Voltage - Maximum	50V DC

### Physical

Card Detection Switch	Open
Card Entry Location	Front
Circuits (Loaded)	6
Circuits (maximum)	6
Durability (mating cycles max)	2500
Ejector Button Side	N/A
Material - Contact	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	High Temperature Thermoplastic
Material - Shell	Stainless Steel

Net Weight	1.613/g
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	Yes
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	1.27mm
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Surface Mount

### Solder Process Data

Max-Duration	10
Lead-Free Process Capability	REFLOW
Max-Cycle	2
Max-Temp	250

---

### Mates With / Use With

#### Mates with Part(s)

Description	Part Number
Mates With	Standard SIM Card