

1627635

https://www.phoenixcontact.com/us/products/1627635

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



CHARX connect basic, Protective cover, square, Accessories, with self-locking mechanism, for attaching to infrastructure charging sockets, Type 2, IEC 62196-2, Front mounting, housing: black, Embossed PHOENIX CONTACT logo

Product description

Self-closing protective cover for infrastructure charging socket

Your advantages

- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- · Individual branding, thanks to the use your own logo
- · Reliable protection of your socket outlet from weather and vandalism
- · Extremely easy assembly, thanks to a front-side screw connection
- · Reduced assembly work, thanks to the pre-injected seal
- No separate panel mounting frame required

Commercial data

Item number	1627635
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBAFC
Catalog page	Page 46 (C-7-2019)
GTIN	4055626346083
Weight per piece (including packing)	108.1 g
Weight per piece (excluding packing)	105 g
Customs tariff number	39269097
Country of origin	PL



https://www.phoenixcontact.com/us/products/1627635



Technical data

Product properties

Product type	Protective cover for Socket Outlet
Product family	CHARX connect basic
Application	for attaching to infrastructure charging sockets
Design (Protective cover)	square
Туре	Accessories
Design	with self-locking mechanism
Affixed logo	Embossed PHOENIX CONTACT logo
Charging standard	Type 2
Charging mode	Mode 3, Case B

Dimensions

Width	85 mm
Height	93.7 mm
Depth	32.5 mm
Width	60 mm
Height	60 mm

Material specifications

Color (Housing)	black (9005)
Material (Housing)	Plastic

Environmental and real-life conditions

Ambient conditions

Degree of protection (Protective cover)	IP54
	IK08
Ambient temperature (operation)	-30 °C 50 °C
Ambient temperature (storage/transport)	-40 °C 80 °C

Standards and regulations

Standards

Standards/regulations	IEC 62196-2

Mounting

Mounting type Protective cover	Front mounting (front screw connection)
Thread type	()
Screws included in the scope of delivery	M4 cylinder head screws Torx-Plus 10IPR





https://www.phoenixcontact.com/us/products/1627635



Drawings

Dimensional drawing






Dimensional drawing



https://www.phoenixcontact.com/us/products/1627635



Dimensional drawing




Hole image

1627635

https://www.phoenixcontact.com/us/products/1627635







Rear mounting with front protective cover screw connection

The screw connection for a protective cover (EV-T2SC-EM) from the accessories range only supports front mounting with a corresponding fixing frame (EV-T2SF-EM). The panel thickness must not exceed 5 mm. The sealing frame that is slid on from the rear must contact the housing panel flush with the flat side and must completely surround the infrastructure socket outlet.



1627635

https://www.phoenixcontact.com/us/products/1627635

Classifications

ECLASS

	ECLASS-11.0	27144792
	ECLASS-12.0	27144792
	ECLASS-13.0	27144792
ET	TIM	
	ETIM 9.0	EC002884
UN	ISPSC	
	UNSPSC 21.0	39121500



https://www.phoenixcontact.com/us/products/1627635



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE
EU REACH SVHC	
	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1627635



Accessories

EV-T2SF-EM - Fixing frame

1627637

https://www.phoenixcontact.com/us/products/1627637



CHARX connect basic, Fixing frame, Accessories, for attaching to infrastructure charging sockets, Type 2, IEC 62196-2, Front mounting, housing: black, Without logo

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com