



**Part Number: 8205**

High-Conductivity Speaker Cable, (1 pr) 12 AWG (7x28) TC, PVC/PVC, CMG

## Product Description

One 20 AWG pair stranded (7x28) tinned copper conductors, twisted pairs, PVC insulation, PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
20	7x28	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.0145 in

#### Color Chart

Number	Color
1	Black & Red

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.18 in	0.025 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
10 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
24.5 pF/ft

#### Current

Max. Recommended Current [A]
3.7 Amps per conductor @ 20°C

#### Voltage

UL Voltage Rating
300V RMS

## Temperature Range

Operating Temp Range:	-20°C To +60°C
-----------------------	----------------

## Mechanical Characteristics

Bulk Cable Weight:	16 lbs/1000ft
Max Recommended Pulling Tension:	28 lbs
Min Bend Radius/Minor Axis:	2 in

## Standards

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4

## Part Number

Plenum (Y/N):	No
---------------	----

## Variants

Item #	Color
8205.0030	CHROME
8205.00U152	CHROME
8205.00U305	CHROME
8205.01152	CHROME
8205.01305	CHROME
8205 060100	CHROME
8205 0601000	CHROME
8205 060500	CHROME
8205 0605000	CHROME
8205 060U1000	CHROME
8205 060U500	CHROME

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.