



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Right Angle**

Connector System: **Board-to-Board**

Number of Positions: **20**

Number of Rows: **2**

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Columns	10
Number of Loaded Positions	20
Stackable	No
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Right Angle
Number of Positions	20
Number of Rows	2



Board-to-Board Configuration

Co-Planar, Orthogonal

Body Features

Connector Profile	Standard
Primary Product Color	Black

Contact Features

Contact Mating Area Length	4 mm[.157 in]
PCB Contact Termination Area Plating Material Thickness	4 – 6 µm[157.48 – 236.22 µin]
Contact Layout	Matrix
Contact Shape & Form	Rectangular
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Tab
Contact Current Rating (Max)	1.7 A

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

Mounting Alignment Feature Length	.75 mm[.029 in]
PCB Mount Alignment Type	Locating Posts
PCB Mount Retention Type	Location Peg
Mating Alignment	With
Mating Alignment Type	Polarization
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Side
Centerline (Pitch)	1.27 mm[.05 in]
Housing Material	LCP

Dimensions

Connector Length	17.78 mm[.7 in]
Connector Height	4.25 mm[.167 in]



Connector Width	10 mm[.394 in]
Profile Height from PCB	4.25 mm[.167 in]
Row-to-Row Spacing	1.27 mm[.05 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Shielded	No
Circuit Application	Power & Signal

Industry Standards

Compatible With Agency/Standards Products	DIN, UL
Compatible With Approved Standards Products	UL
Industry Standard	IEC
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Reel Diameter	330 mm[12.99 in]
Packaging Quantity	560
Packaging Method	Tape & Reel

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability







Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as





EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 168312-E IDCCS SMC 1,27 20 * AU AUI 100 PVC	 TE Part # 168315-E IDCCS SMC 1,27 20 * AU AUI 300 PVC	 TE Part # 354056-E SMCB 20 F AB VV 7-13 CL * H007 137 E002	 TE Part # 354063-E SMCB 20 F AB VV 7-03 CL * H007 137 E002
 TE Part # 354071-E SMCB 20 F AB VV 7-23 CL * H007 137 E002	 TE Part # 354079-E SMCQ 20 F AB VV 7-03 CL * 0007 137 E002	 TE Part # 354094-E SMCB 16 M AB VV 7-03 CL * 0007 137 E004	 TE Part # 354096-E SMCB 32 M AB VV 7-03 CL * 0007 137 E004
 TE Part # 354097-E SMCB 40 M AB VV 7-03 CL * 0007 137 E004	 TE Part # 294814-E SMCB 20 F AB VV 6-01 VH * 0008 137 E002		

Also in the Series | ERNI SMC

 Board-In Connectors(6)	 Connector Adapters & Connector Savers(45)	 PCB Headers & Receptacles(81)	 Pluggable I/O Cable Assemblies(27)
---	---	--	---



Wire-to-Board Connector Assemblies
& Housings(5)

Customers Also Bought



TE Part #9-1879208-4
CPF 0402 75K 0.1% 25PPM 1K RL




TE Part #7-1879208-0
CPF 0402 7K5 0.1% 25PPM 1K RL



TE Part #2-2141272-1
2POS, MIXED,HEADER ASSY,CODA



TE Part #1-1719101-1
PCB 9.5 TERMINAL SN



TE Part #234834-E
SRCA 2,54 2 M 1 SMD 137 E1 167 *
GURT *



TE Part #254417-E
SMCQ 40 M AB VV 8-23 CL * H007 137
E005



TE Part #254588-E
SMCQ 20 M AB VV 8-13 CL * H007 137
E005



TE Part #374317-E
DRCB 2,54 20 M SMD * 137 E012 094
GURT *



TE Part #4-2331712-1
2POS,PCON21,HDR ASSY,COD A

Documents

Product Drawings

SMCB 20 M AB VV 7-03 CL * 0007 137 E004

English

SMCB 20 M AB VV 7-03 CL * 0007 137 E004

German

CAD Files

Customer View Model

ENG_CVM_CVM_354095-E_1.3d_stp.zip



English

Customer View Model

[ENG_CVM_CVM_354095-E_1.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_354095-E_1.3d_igs.zip](#)

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Datasheet - ERNI SMC 1.27mm Connectors](#)

English

[Datasheet - ERNI SMC 1.27mm Connectors](#)

German

Product Specifications

[SMC_Receptacle_with_Ribbon_Cable_IDC_and_Header](#)

English