

## Plastic label - US-EMLP (27X15) SR - 0828894

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plastic label, Card, silver, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: Adhesive, Lettering field: 27 x 15 mm



The figure shows a version of the article

### Why buy this product

- ✓ The US-EMLP ... UniSheet labeling range includes self-adhesive device markers with good adhesive properties
- ✓ The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- ✓ The perforated markers are easy to separate and can be easily fitted
- ✓ The sheets provide space for including function texts



### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 pc                                                                                                   |
| Minimum order quantity               | 10 pc                                                                                                   |
| GTIN                                 | <br>4 046356 558976 |
| Weight per Piece (excluding packing) | 17.81 g                                                                                                 |
| Custom tariff number                 | 39199000                                                                                                |
| Country of origin                    | Germany                                                                                                 |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length (b) | 26.9 mm |
| Height     | 0.5 mm  |
| Width (a)  | 14.9 mm |

#### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -30 °C ... 80 °C |
| Ambient temperature (assembly)  | 15 °C ... 25 °C  |

#### General

## Plastic label - US-EMLP (27X15) SR - 0828894

### Technical data

#### General

|                                                              |                                  |
|--------------------------------------------------------------|----------------------------------|
| Color                                                        | silver                           |
| Components                                                   | Silicone-free                    |
| Inflammability class according to UL 94                      | V0                               |
| Material                                                     | PVC                              |
| Wipe resistance                                              | DIN EN 61010-1 (VDE 0411-1)      |
| Number of individual labels                                  | 27                               |
| Number of individual labels per row                          | 3                                |
| RoHS compliant                                               | Yes                              |
| Adhesive                                                     | Acrylic                          |
| Printability                                                 | Thermal transfer                 |
| Device                                                       | 5146464 THERMOMARK CARD          |
|                                                              | 5146451 THERMOMARK CARD-US-MAG1  |
| Ink ribbon                                                   | 0801371 THERMOMARK-RIBBON 110-TC |
| Test specification weathering-resistance                     | Following ISO 4892-2:2013-03     |
| Test duration                                                | 96 h                             |
| Wipe resistance test result                                  | Test passed                      |
| Salt spray test specification                                | DIN EN ISO 9227:2012-09          |
| Test duration                                                | 96 h                             |
| Salt spray testing result                                    | Test passed                      |
| Alternating condensation climate with SO2 test specification | DIN 50018:2013-05                |
| Climate level                                                | AHT 1.0 S                        |
| Cycles                                                       | 2                                |
| Condensation test result                                     | Test passed                      |
| Wipe resistance of test specification inscriptions           | IEC 61010-1:2010-06              |
| Result                                                       | Test passed                      |
| Burning behaviour                                            | self-extinguishing               |
| Foil strength                                                | 500 µm                           |
| Adhesive strength                                            | 50 µm                            |
| Marking mounting type                                        | Adhesive                         |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |

## Plastic label - US-EMLP (27X15) SR - 0828894

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Accessories

#### Accessories

#### Magazine

Magazine - THERMOMARK CARD-US-MAG1 - 5146451



Magazine for the THERMOMARK CARD printer, for accommodating US cards

---

#### Marker carriers

Marker carriers - CARRIER-EMP 22 (27X15) - 0827447



Marker carriers, black, unlabeled, Mounting type: Screws, rivets, Diameter: 22 mm, Lettering field: 27 x 15 mm

---

Marker carriers - CARRIER-EMLP 22 (27X15) - 0828986



Marker carriers, black, unlabeled, Mounting type: Screws, rivets, Diameter: 22 mm, Lettering field: 27 x 15 mm

---

