SIEMENS

Data sheet

6ES7972-0BB70-0XA0

product type designation product description



PROFIBUS connector

PROFIBUS bus connector, RS 485, Fast Connect, with programming port, 90° SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, 15.8x 72.2x 36.4 mm (WxHxD), Insulation displacement method FastConnect, With PG receptacle

suitability for use	For connecting PROFIBUS stations to the PROFIBUS bus cable
transfer rate	
transfer rate / with PROFIBUS DP	9.6 kbit/s 12 Mbit/s
interfaces	
number of electrical connections	
 for PROFIBUS cables 	2
 for network components or terminal equipment 	1
type of electrical connection	
 for PROFIBUS cables 	Integrated insulation displacement terminals for 2-core PB FC installation cables
 for network components or terminal equipment 	9-pin sub D connector
type of electrical connection / FastConnect	Yes
mechanical data	
design of terminating resistor	Resistor combination integrated and connectable via slide switch
material / of the enclosure	plastic
locking mechanism design	Screwed joint
design, dimensions and weights	
type of cable outlet	90 degree cable outlet
width	15.8 mm
height	72 mm
depth	36.4 mm
net weight	45 g
ambient conditions	
ambient temperature	
during operation	-25 +60 °C
 during storage 	-40 +70 °C
during transport	-40 +70 °C
protection class IP	IP20
product features, product functions, product components / gen	eral
product feature	
silicon-free	Yes
product component	
 PG connection socket 	Yes
strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
RoHS conformity	Yes
UL approval	Yes

reference code	
 according to IEC 81346-2 	XG
urther information / internet links	
internet link	
 to website: Selection guide for cables and connectors 	https://support.industry.siemens.com/cs/ww/en/view/109766358
 to web page: selection aid TIA Selection Tool 	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com
 to website: Image database 	https://www.automation.siemens.com/bilddb
 to website: CAx-Download-Manager 	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
ecurity information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product versions are used. Use of product versions that are
pprovolo / Cartificateo	no longer supported, and failure to apply the latest updates may increase
Approvals / Certificates	no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
pprovals / Certificates General Product Approval	no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under

last modified:

8/8/2024 🖸