



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.31 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Steel
Terminal Plating Material	Nickel
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	15.11 mm[.595 in]
Compatible Insulation Diameter Range	2.29 – 3.3 mm[.09 – .13 in]
Wire Size	.51 – 1.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, RU (UL Component Program), UL
Compatible With Approved Standards Products	UL E66717

Packaging Features

Packaging Quantity	18000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 2-480435-3 187 FASTON HSG.,REC.,1 POS,BLACK	 TE Part # 2-480435-2 187 FASTON HSG.,REC.,1 POS,NATURAL	 TE Part # 2150007-1 OCEAN_2.0_Applicator-E-090F140F-REM	 TE Part # 1-480435-0 FASTON 187 REC HSG NYLON NAT
 TE Part # 2150007-2 OCEAN_2.0_Applicator-E-090F140F-REA	 TE Part # 480435-2 187 FASTON HSG. REC 1P BLACK	 TE Part # 7-2150007-7 OCEAN_2.0_SPARE_PART_KIT-090F140F	

Also in the Series | FASTON 187

 Crimp Terminal Housings(41)	 Insertion & Extraction Tools(1)	 Joints & Splices(1)	 PCB Terminals(42)
---------------------------------	-------------------------------------	-------------------------	-----------------------



Quick Disconnects(208)




Splices(1)


Customers Also Bought



TE Part #1-5177983-2
0.8FH,R05H.5,060,15/Sn,TU



TE Part #3-643814-4
04P MTA100 CONN ASSY POL RIB



TE Part #640550-2
02P MTA100 COVER




TE Part #292173-8
CT BOX HDR H SMT 8P O/TAPE BLA



TE Part #T4061120003-002
M8 CABLE ST M 1.0M 3POS PUR CABLE



TE Part #2238041-1
187 FASTON,REC.,20-16 AWG,NPST



TE Part #9354653001
55A9002-30-5



TE Part #952651-000
B-106-1501



TE Part #3-5353515-0
ON TAPING (EMBOSS) 0.5MM FS CONN. TAB AS



TE Part #CSI-RGFB-300-UFFR
RP-SMA to U.FL/MHF1 300mm 1.13 OD

Documents

Product Drawings

187 FASTON,REC.,20-16 AWG,NPST

English

CAD Files

Customer View Model

ENG_CVM_CVM_1742841-1_A.2d_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG_CVM_CVM_1742841-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1742841-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[1-1773948-2 Standard Line FASTON Receptacles QRG](#)

English

[Introductory Flyer - Low Insertion Force FASTON Terminals](#)

English

Product Specifications

[Application Specification](#)

English

[FASTIN-FASTON 110, 187, 205 And 312 Series Receptacle Contacts](#)

English

[Application Specification](#)

English