TE Internal #: 413990-1

SMB RF Interface, Jack, 50 ohm, Snap-Fit, Cable-to-Board, 1

Position, Printed Circuit Board, Board Mount, -65 – 85 °C [-85 – 185 °

F], Brass, Plated

View on TE.com >



Connectors > RF Connectors > Coax Connectors > SMB Connector: Jack, Vertical Mount, Mated Outer Dia. 4.75mm, 50 Ohm











RF Interface: SMB

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 4.75 mm [.187 in]

Impedance: 50Ω

RF Connector Coupling Mechanism: Snap-Fit

All SMB Connector: Jack, Vertical Mount, Mated Outer Dia. 4.75mm, 50 Ohm (2)

Features

Product Type Features

Connector Shape	Rectangular
Connector Product Type	Connector Assembly
RF Interface	SMB
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	50 Ω	



Body Features

Body Underplating Material	Nickel
Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Gold

Contact Features

RF Connector Center Contact Underplating Material	Nickel
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Brass

Termination Features

Termination Post & Tail Length	3.94 mm[.155 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

RF Connector Coupling Mechanism	Snap-Fit
Connector Mounting Type	Board Mount
Detent	Without

Dimensions

Profile Height from PCB	7.62 mm[.3 in]
RF Connector Mated Outer Diameter (Approximate)	4.75 mm[.187 in]

Usage Conditions

Out and the set Tanana and the set Danas	/F 0F 0C[0F 10F 0F]
Operating Temperature Range	-65 – 85 °C[-85 – 185 °F]

Packaging Features

Packaging Method	Carton
------------------	--------

Other

Grade	Mil-Type
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2024
(241)

Candidate List Declared Against: JUNE
2024 (241)

SVHC > Threshold:
Pb (3.7% in Component Part)

Article Safe Usage Statements:
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Bromine/Chlorine - Br and Cl < 900

ppm per homogenous material. Also BFR

/CFR/PVC Free

Solder Process Capability Pin-in-Paste capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts








Customers Also Bought





















Documents

Product Drawings

STR JACK, SMB, PCB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_413990-1_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_413990-1_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_413990-1_J.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SMB Connectors

English

Product Specifications

Product Specification

English

Product Specification

English

SMB RF Interface, Jack, 50 ohm, Snap-Fit, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount, -65 – 85 °C [-85 – 185 °F], Brass, Plated



Instruction Sheets

Instruction Sheet (U.S.)

English

AMP SMB PRINTED CIRCUIT (PC) BOARD VERTICAL JACK CONNECTOR P/N 413990

English