

SENCITY® Road MIMO

1399.99.0128

Properties

- Rugged vehicle rooftop multi-band antenna for heavy duty vehicles like bus and truck
- Supports WiFi 2.4, 5 GHz and IEEE 802.11p in 3x3 MIMO configurations.
- Single hole mounting, easy cabling feed-through.
- Works also on non-metallic surfaces.

**Electrical bands**

	Band 1	Band 2
Frequency (MHz)	2400 MHz ... 2690 MHz	4900 MHz ... 5935 MHz
Impedance	50 Ω	50 Ω
VSWR	1.8	1.8
Gain (dBi)	6 dBi	7 dBi
Isolation between Ports	14 dB	22 dB
Ambient Temperature	25 °C	25 °C
Composite Power max	40 W	30 W

Ports

	Port 1	Port 2	Port 3
Connector	SMA, jack (female)	SMA, jack (female)	SMA, jack (female)
Cable type	ENVIROFLEX_316_D -AM	ENVIROFLEX_316_D -AM	ENVIROFLEX_316_D -AM
Cable length	0.3 m	0.3 m	0.3 m
Polarization	vertical	vertical	vertical
DC grounded	Yes	Yes	Yes

Connections

Port number	Port 1	Port 2	Port 3
Band 1	✓	✓	✓
Band 2	✓	✓	✓

SENCITY® Road MIMO

1399.99.0128

Mechanical data	
Weight	0.41 kg
Dimensions	82 mm x 83 mm x 208 mm (Height x Width x Depth)

Interface and material data	
Radome material	ASA (acrylic ester-styrene-acrylonitrile)
Radome colour	RAL 7043 (dark grey)
Back plate/base plate material	Aluminium

Environmental data	
Operation temperature	-40 °C ... 85 °C
Storage temperature	-40 °C ... 85 °C
Transport temperature	-40 °C ... 85 °C
Ingress protection (IP Rating)	Mated / IP68, IP69
Flammability rating	ECE-R118
Solar radiation	DIN 75220
Standards	Automotive ISO 16750

Environmental remarks	
ISO 16750:2010 environmental tests	
MIL-F-14072D low corrosion design	
E-Mark	
CE-Mark	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P38213 / Date of publication: 29.01.2024 / uncontrolled copy