



CH SHENYANG ELECTRONICS

APPROVAL APPLICATION

|                    |                     |        |
|--------------------|---------------------|--------|
| 厂商编码<br>Number in: | ONA-CM008-H         |        |
| 客户编码<br>Item Name: | /                   |        |
| 产品名称<br>Type:      | CM Inductance       |        |
| 规格型号<br>Client:    | 15A 8100uH ±30% 10K |        |
| 编制日期<br>Date:      | 2024.09.10          | REV: A |
| 修改日期<br>Date:      |                     | REV:   |

|                             |       |        |            |
|-----------------------------|-------|--------|------------|
| APPROVED FOR CUSTOMER 客户认可: |       |        |            |
| ED 工程                       | TD 质量 | R&D 研发 | APPROVE 批准 |
|                             |       |        |            |
| PRODUCERS CONFIRMED 制造商认可:  |       |        |            |
| ED 工程                       | TD 质量 | R&D 研发 | APPROVE 批准 |
|                             |       |        |            |

Shanghai Shen Yang Electronic Technology Co., Ltd.

principal: YUE HUAN HE

Cel: 17301628729 Tel: 17301628729

QQ: 313987220 E-MAIL: [shshenyangdzkj@hotmail.com](mailto:shshenyangdzkj@hotmail.com)

Address: Building 5-7, No. 593 Kegong Road, Zhelin Town, Fengxian District, Shanghai

<http://www.shenyang-elecironic.com/>

|                                                                                                                                                      |                             |                                     |                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------|------------------|
| <div> CH SHENYANG ELECTRONICS</div> <div>APPROVAL APPLICATION</div> |                             | Customer:                           | /                |
|                                                                                                                                                      |                             | REV:                                | A                |
| product name/Type:                                                                                                                                   |                             | CM Inductance / 15A 8100uH ±30% 10K | Date: 2024.09.10 |
| HISTORY OF CHANGED 修改记录                                                                                                                              |                             |                                     |                  |
| REV 版本                                                                                                                                               | DESCRIPTION OF CHANGES 修改内容 | CHANGE REASON 原因                    | DATE 日期          |
| A                                                                                                                                                    | New issue                   | /                                   | 2024.09.10       |
|                                                                                                                                                      |                             |                                     |                  |
|                                                                                                                                                      |                             |                                     |                  |
|                                                                                                                                                      |                             |                                     |                  |
|                                                                                                                                                      |                             |                                     |                  |




Customer: /

REV: A


product name/Type: CM Inductance / 15A 8100uH  $\pm 30\%$  10K

Date: 2024.09.10


Material size chart (unit:mm)/Construction



Front view



Side view



Bottom view

| NO.             | Model (uH)                   | A<br>(max) | B<br>(max) | C<br>(max) | D<br>( $\pm 0.5$ ) | E ( $\pm$<br>0.5) | F ( $\pm$<br>0.5) | G ( $\pm$<br>0.3) | H ( $\pm$<br>0.3) | I ( $\pm$<br>0.2) | J ( $\pm$<br>0.2) | Weight<br>(g) |
|-----------------|------------------------------|------------|------------|------------|--------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|---------------|
| ONA-CM0<br>08-H | 15A 8100uH<br>$\pm 30\%$ 10K | 31         | 21         | /          | 9                  | 25                | 3.5               | /                 | /                 | /                 | 1.8               | 28.9          |

“A” Significant size; Mark: ONA-CM008-H CHSHENYANG Y/W  
注意事项:

**Process requirements**

- 1, Product Appearance 100% Inspection Test;
- 2, Electrical Performance 100% Inspection Test;
- 3, RoHS、UL94 ( in line with EU standards) ;
- 4, Reliable Performance Reference AEC-Q200 Standard Test;
- 5, Storage temperature and humidity:  $< 35^{\circ}\text{C}$ ; 35-65% RH
- 6, working temperature range  $:-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$ ;



Customer:

/

REV:

A

product name/Type:

CM Inductance / 15A 8100uH  $\pm 30\%$  10K

Date:

2024.09.10

## Electrical characteristic

| NO | Non-woven 挡墙 | Wire(电流) | Turns (匝比) | START 起线 | FINISH 尾线 | Tape 胶带 | Case 套管 |   | Note |
|----|--------------|----------|------------|----------|-----------|---------|---------|---|------|
|    |              |          |            |          |           |         | S       | F |      |
| N1 | /            | 15A      | 1: 1       | 1        | 2         | /       | /       | / |      |
| N2 | /            | 15A      | 1: 1       | 4        | 3         | /       | /       | / |      |

| Project                                | unit | Test Conditions                          | MIN            | MAX   | test instrument | Note |
|----------------------------------------|------|------------------------------------------|----------------|-------|-----------------|------|
| L 1-2&4-3                              | uH   | 10KHz,0.3V, Ser                          | 5670           | 10530 | GKT3259         | ●    |
|                                        |      |                                          | 8100±30%       |       |                 |      |
| LK 1-2&4-3                             | uH   | 10KHz,0.3V, Ser                          | 11.24（REF）     |       | GKT3259         | ○    |
| Fight Voltage（AC*1.2, 3S, Can replace） | mA   | PRI-SEC,AC2000V,1min,0.5mA ,50/60Hz      | No abnormality |       | 19053           | ○    |
|                                        | mA   | PRI/SEC-Core,AC1500V,1min,0.5mA ,50/60Hz | No abnormality |       | 19053           | ○    |
| DCR 1-2&4-3                            | m Ω  | 25℃                                      | 7（REF）         |       | GKT3259         | ○    |
| Insulation resistance                  | G Ω  | PRI-SEC DC1000V,10s,1G Ω                 | No abnormality |       | 19053           | ○    |
|                                        | G Ω  | PRI/SEC-Core DC1000V,10s,1G Ω            | No abnormality |       | 19053           | ○    |

“●”代表关键特性 Important performance, “○”代表一般特性 General performance



CH SHENYANG ELECTRONICS

APPROVAL APPLICATION

Customer:

/

REV:

A




product name/Type:

CM Inductance / 15A 8100uH  $\pm 30\%$  10K

Date:

2024.09.10

Electrical performance test (Reference data)





CH SHENYANG ELECTRONICS

## APPROVAL APPLICATION

Customer:  
REV:

/

A

product name/Type:

CM Inductance / 15A 8100uH ±30% 10K

Date:

2024.09.10

## Reliability Test

| 序号 | 应力方式                                        | 检测方法                                                                  | 数量 Size | Number of Lots 批数 | 接受标准 Accept Criteria |
|----|---------------------------------------------|-----------------------------------------------------------------------|---------|-------------------|----------------------|
| 1  | Electrical performance 前后电气性能               | AEC-Q200/规格书要求 (Specification)                                        | all     | all               | 0 Fails              |
| 2  | High Temperature Exposure (Storage) 高温存储    | MIL-STD-202 Method 108 (125°C, 1000H)                                 | 77      | 1                 | 0 Fails              |
| 3  | Temperature Cycling 温度循环                    | JESD22 Method JA- 104 (-40~125°C, Every 30minutes)                    | 77      | 1                 | 0 Fails              |
| 4  | Biased Humidity 偏高湿度                        | MIL-STD-202 Method 103 (85°C 85%RH, 1000H)                            | 77      | 1                 | 0 Fails              |
| 5  | High Temperature Operation Life Test 高温运行寿命 | MIL-PRF-27 (125°C, 1000H, Rating Current)                             | 77      | 1                 | 0 Fails              |
| 6  | External Visual 外观                          | MIL-STD-883 Method 2009 (Specification)                               | all     | all               | 0 Fails              |
| 7  | Physical Dimension 结构尺寸                     | JESD22 Method JB- 100 (Specification)                                 | 30      | 1                 | 0 Fails              |
| 8  | Terminal Strength (Leaded) 端子强度 (引脚)        | MIL-STD-202 Method 211 (17.7N, 60s)                                   | 30      | 1                 | 0 Fails              |
| 9  | Resistance to Solvents 溶剂抵抗                 | MIL-STD-202 Method 215 (The solvent, Brush 2-3 times)                 | 5       | 1                 | 0 Fails              |
| 10 | Mechanical Shock 机械冲击                       | MIL-STD-202 Method 213 (100G, 6ms, 3 axes and 6 directions, 3 times ) | 30      | 1                 | 0 Fails              |
| 11 | Resistance to Soldering Heat 耐热焊接           | MIL-STD-202 Method 210 (260°C, 10S, 0.5inch)                          | all     | all               | 0 Fails              |
| 12 | Vibration 震动                                | MIL-STD-202 Method 204 (10HZ-2000HZ-10HZ, 5G, 4H, 3 Directions.)      | 30      | 1                 | 0 Fails              |
| 13 | ESD 静电放电                                    | AEC-Q200-002 or ISO/DIS (6KV Air discharge)                           | 15      | 1                 | 0 Fails              |
| 14 | Solderability 可焊性                           | J-STD-002 (8H*155°C, 235°C, 5s, >95%)                                 | 45      | 1                 | 0 Fails              |
| 15 | Flammability 可燃性                            | UL-94 (UL report)                                                     | 6       | 1                 | V-1 or V-0           |
| 16 | Board Flex 板弯曲                              | AEC-Q200-005 ( (D) x=2 mm, 60+5S)                                     | 30      | 1                 | 0 Fails              |