



SCALANCE XF204 managed two BusAdapters BA 2xRJ45 HA IEC 62443-4-2 certified; IE switch, 4 x 10/100 Mbps, 2 x BusAdapter interface, error signaling contact, set pushbutton, redundant 24 V DC power supply, PROFINET device, extended temperature range -40 °C...+70 °C, conformal coating, with electronic manual on DVD, C-PLUG optional, delivery with BusAdapter. 6DL1193-6AR00-0AA0

| product type designation | |
|--|-----------------------------------|
| product brand name | SCALANCE |
| product type designation | XF204 |
| transfer rate | |
| transfer rate | 10 Mbit/s, 100 Mbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| • for network components or terminal equipment | 4 |
| interfaces / other | |
| number of electrical connections | |
| • for signaling contact | 1 |
| • for power supply | 1 |
| type of electrical connection | |
| • for signaling contact | 2-pole terminal block |
| • for power supply | 2-pole terminal block |
| design of the removable storage | |
| • C-PLUG | Yes |
| operating voltage / of the signaling contacts | |
| • at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| • at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| product component / connection for redundant voltage supply | Yes |
| type of voltage / 1 / of the supply voltage | DC |
| • supply voltage / 1 / rated value | 24 V |
| • power loss [W] / 1 / rated value | 8.6 W |
| • supply voltage / 1 / rated value | 19.2 ... 28.8 V |
| • consumed current / 1 / maximum | 0.36 A |
| • type of electrical connection / 1 / for power supply | 2-pole terminal block |
| • product component / 1 / fusing at power supply input | Yes |
| • fuse protection type / 1 / at input for supply voltage | 2.5 A (cannot be changed by user) |
| ambient conditions | |
| ambient temperature | |
| • during operation | -40 ... +70 °C |
| • during storage | -40 ... +85 °C |
| • during transport | -40 ... +85 °C |
| relative humidity | |
| • at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |

design, dimensions and weights

| | |
|-----------------------------------|---------|
| design | compact |
| width | 100 mm |
| height | 117 mm |
| depth | 74 mm |
| net weight | 0.25 kg |
| fastening method | |
| • 35 mm top hat DIN rail mounting | Yes |
| • wall mounting | No |
| • S7-300 rail mounting | No |
| • S7-1500 rail mounting | No |

product features, product functions, product components / general

| | |
|---|---|
| cascading in the case of a redundant ring / at reconfiguration time of $\leq 0.3\text{ s}$ | 50 |
| cascading in cases of star topology | any (depending only on signal propagation time) |

product functions / management, configuration, engineering

| | |
|--|-----|
| product function | |
| • CLI | Yes |
| • web-based management | Yes |
| • MIB support | Yes |
| • TRAPs via email | Yes |
| • configuration with STEP 7 | Yes |
| • port mirroring | Yes |
| • multipoint mirroring | Yes |
| • PROFINET IO diagnosis | Yes |
| • switch-managed | Yes |
| PROFINET conformity class | B |
| protocol / is supported | |
| • Telnet | Yes |
| • HTTP | Yes |
| • HTTPS | Yes |
| • TFTP | Yes |
| • FTP | No |
| • BOOTP | No |
| • DCP | Yes |
| • LLDP | Yes |
| • SNMP v1 | Yes |
| • SNMP v2 | Yes |
| • SNMP v3 | Yes |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 - higher level designation/location designation | Yes |

product functions / diagnostics

| | |
|--------------------------|-----|
| product function | |
| • port diagnostics | Yes |
| • statistics Packet Size | Yes |
| • statistics packet type | Yes |
| • error statistics | Yes |

product functions / DHCP

| | |
|------------------|-----|
| product function | |
| • DHCP client | Yes |

product functions / redundancy

| | |
|--|-----|
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product function | |
| • media redundancy protocol (MRP) with redundancy manager | Yes |
| • Media Redundancy Protocol Interconnection (MRP-I) | Yes |
| • Media Redundancy Protocol for Planned Duplication (MRPD) | No |
| • of the PROFINET IO device / is supported / H-Sync forwarding | Yes |
| • of the PROFINET IO device / is supported / PROFINET | Yes |

| | |
|---|--|
| system redundancy | |
| • ring redundancy | Yes |
| • high speed redundancy protocol (HRP) with redundancy manager | Yes |
| • high speed redundancy protocol (HRP) with standby redundancy | Yes |
| • redundancy procedure RSTP+ | Yes |
| • Parallel Redundancy Protocol (PRP)/operation in the PRP-network | No |
| • Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |
| • passive listening | Yes |
| product functions / security | |
| protocol / is supported | |
| • SSH | Yes |
| product functions / time | |
| product function | |
| • SICLOCK support | No |
| protocol / is supported | |
| • NTP | No |
| • SNTP | Yes |
| standards, specifications, approvals | |
| certificate of suitability | |
| • CE marking | Yes |
| • KC approval | Yes |
| standard | |
| • for EMC interference emission | EN 61000-6-4:2001 (Class A) |
| • for immunity to EMC | EN 61000-6-2, EN 61000-6-4 |
| • for safety / from CSA and UL | UL 61010-2-201 |
| standards, specifications, approvals / other | |
| certificate of suitability | |
| • railway application in accordance with EN 50124-1 | No |
| IT security for industrial automation systems / according to IEC 62443-4-2:2019 | Yes |
| product functions / general | |
| reference code | |
| • according to IEC 81346-2 | KF |
| • according to IEC 81346-2:2019 | KFE |
| Warranty period | 5 a |
| further information / internet links | |
| internet link | |
| • to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| • to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| • to website: Industrial communication | https://www.siemens.com/simatic-net |
| • to web page: SiePortal | https://sieportal.siemens.com/ |
| • to website: Image database | https://www.automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | https://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)

[Declaration of Con-
formity](#)

last modified:

8/16/2024 