


## Cylindrical Surface Mount Zerohm Jumpers

### ZCHP Series

- Reliable Metal Glaze™ technology
- Available in all standard CHP sizes
- Superb solderability - reflow and wave
- Operating temperature -55°C to +150°C



# OBSOLETE

All Pb-free parts comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

## Applications

Zerohm Jumpers or Crossovers are basically interconnection devices between points on a PC board. Typically, they are used to connect two points on a PC board due to other circuit paths which must be crossed over. The XCHP Jumpers are available in four case sizes and are supplied on tape and reel to support high volume placement.

## Electrical Data

Size Code	Industry Footprint	IRC Type	Maximum Resistance (mΩ)	Current Rating @ 25°C (amps) <sup>2</sup>
B	1206	ZCHP 1/8	20	3
D	2010	ZCHP 1/2	30	4
F	2512	ZCHP 1	35	5
H	3610	ZCHP 2	35	6

<sup>2</sup> Derate current to "0" amps at 150°C.

## Ordering Procedure

Example: ZCHP1LF13 (ZCHP1, Pb-free)



1 Type	2 Termination	3 Packing	
ZCHP1/8	Omit for SnPb	Standard packing	
ZCHP1/2	LF = Pb-free	7	ZCHP1/8 2500/7" reel
ZCHP1		7	ZCHP1/2 & 1 1500/7" reel
ZCHP2		13	ZCHP2 1500/13" reel
		Non-standard packing	
		13	ZCHP1/8, 1/2 & 1 5000/13" reel

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TT Electronics:](#)

[ZCHP-2-7](#) [ZCHP-1/8-7](#) [ZCHP-1/2-7](#) [ZCHP-1-7](#) [ZCHP-2-13](#)