


编 号	尺寸 (mm)	
	A	B
HC-SPH-2*2Y	2.00	6.00
HC-SPH-2*3Y	4.00	8.00
HC-SPH-2*4Y	6.00	10.00
HC-SPH-2*5Y	8.00	12.00
HC-SPH-2*6Y	10.00	14.00
HC-SPH-2*7Y	12.00	16.00
HC-SPH-2*8Y	14.00	18.00
HC-SPH-2*9Y	16.00	20.00
HC-SPH-2*10Y	18.00	22.00
HC-SPH-2*11Y	20.00	24.00
HC-SPH-2*12Y	22.00	26.00

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material:Houing Nylon66, UL94V-0

制图 DRAWN	变更内容 DESCRIPTION	日期 DATE	GENERAL TOLERANCE		制图 DRAWING	钱岳生 2013、11、01		料号 PART NO.	HC-SPH-2*NY		版本 REV.	A				
			X.±0.25	X.*±2'		审核 CHECK	张名 2013、11、03		品名 TITLE	SPH孔座		页次 SHEET	1/1			
			.X±0.20	.X*±1'			核准 APPROVAL			张名 2013、11、05			客户料号 CUTL NO.			
			.XX±0.15	.XX*±0.5'						单位 UNITS						MM
			.XXX±0.10	.XXX*±0.5'		深圳市华灿天禄电子有限公司										