



PVC hose with rigid PVC spiral and copper wire for making the hose antistatic, for delivery and suction of food liquids.



**SMOOTH SURFACES**

\*\*\*\*\*



**FLEXIBILITY**

\*\*\*



**ABRASION RESISTANCE**

\*\*\*\*



**TEMPERATURE RANGE**

-5°C +60°C  
23°F +140°F



**CHEMICAL RESISTANCE**

PVC table



**CRUSHING RESISTANCE**

\*\*\*



**ANTISTATIC**

Wire resistance 0,075 Ohm/m



**FOR FOOD**

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 40°C for 24 hours.

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	VACUUM 23°C	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	m h2o	mm		m	
	18	24	3	260	70	8	7	6	right	50	ON DEMAND
	20	26.2	3.1	275	75	8	7	6.5	right	50	ON DEMAND
	22	28.4	3.2	300	80	/	/	7	right	50	ON DEMAND
1	25	31.6	3.3	330	120	8	7	7.4	right	50	ON DEMAND
	30	37	3.5	420	140	7	7	7.5	right	50	ON DEMAND
1 1/4	32	39.2	3.6	460	150	7	7	7.7	right	50	ON DEMAND
	35	42.2	3.6	500	160	7	7	7.7	right	50	ON DEMAND
1 1/2	38	45.4	3.7	550	170	6	7	7.6	right	50	ON DEMAND
	40	47.6	3.8	610	180	6	7	7.8	right	50	ON DEMAND
1 3/4	45	52.4	3.7	670	200	6	7	8	right	50	ON DEMAND
2	50	58.2	4.1	810	220	6	7	8.3	right	50	ON DEMAND
2	51								right	50	ON DEMAND
	55	63.6	4.3	860	248	6	7	9.8	right	50	ON DEMAND
	60	68.4	4.2	970	270	5	7	8.5	right	50	ON DEMAND
2 1/2	63	71.5	4	1040	290	5	7	8.5	right	50	ON DEMAND
	70	78.4	4.2	1200	320	4	7	9	right	50	ON DEMAND
	75	85.4	5.2	1380	350	4	7	9.5	right	50	ON DEMAND
3	76								right	25	ON DEMAND
	80	90.6	5.3	1560	360	4	7		right	25	ON DEMAND
3	89								right	25	ON DEMAND
3	90	100.6	5.3	1850	430	4	7		right	25	ON DEMAND
	100	112	6	2200	480	4	7		right	25	ON DEMAND
4	102	114.2	6.3	2160	480	4	7		right	25	ON DEMAND
	110	122	6	2500	530	4	5		right	25	ON DEMAND
	120	132.4	6.2	2850	680	3	5		right	25	ON DEMAND
	125	137.6	6.3	3130	730	3	5		right	25	ON DEMAND
5	127	127	6.8	3130	/	3	5		right	25	ON DEMAND
	150	164.2	7.2	4250	810	3	5		right	25	ON DEMAND
6	152	167.2	7.4	4250	/	3	5		right	25	ON DEMAND
	200	218.2	9.1	6400	900	2	5		right	10	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.