

[Connectors](#) > [Circular Connectors](#) > [Standard Circular Connectors](#)

PLUG. BOOT TERMIN. TYPE 6 AS SIZE 7. CAD

✓ **ACTIVE**

[DEUTSCH](#) | [AS Standard](#)

TE Part # **AS607-35PN-913F**

TE Internal #: **AS607-35PN-913F**

Product Type : **Connector**

Connector System : **Wire-to-Wire**

Number of Positions : **6**

Sealable : **Yes**

Shell Plating Material : **Cadmium, O.D.**

 [Add to List](#) ▼

[Similar Products](#)



ORDER SAMPLES

Compatible Parts & Tooling

SHOP OUR DISTRIBUTORS

North America ▼

Request pricing, availability and customization options

CONTACT US



We are here to help!

Get in touch with our product experts.



CHAT WITH US



EMAIL US



CALL US

DOCUMENTS

FEATURES

PRODUCT COMPLIANCE

Catalog
Pages/Data
Sheets



[ENG_DS_1-1773721-8_as_interconnection_0417.pdf](#) English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type
Features

Assembly Type : **Electrical Connector**

Product Type : **Connector**

Connector System : **Wire-to-Wire**

Sealable : **Yes**

Shell Size : **7**

Connector Style : **Plug**

Shell Type : **Metal**

Configuration
Features

Number of Positions : **6**

Preloaded : **No**

Keying : **Key Polarization N**

Factory Installed Backshell :





Body Features	<p>Feedthrough Type : No</p> <p>Entry Style : Rear Insertion</p> <p>Shell Plating Material : Cadmium, O.D.</p> <p>Shell Material : Aluminum Alloy</p> <p>Insulation Material : Hard Dielectric/Silicone</p> <p>Hermetically Sealed : No</p> <p>Environmental Protection Type : Sealed</p> <p>Environmental Protection : With</p>
Contact Features	<p>Contact Layout Arrangement : 7 – 35</p> <p>Contact Type : Pin</p> <p>Contact Quantity (Size 22D) : 6</p>
Mechanical Attachment	<p>Polarization Code : N</p> <p>Mating Alignment Type : Keyed</p> <p>Mating Retention : With</p> <p>Mating Alignment : With</p> <p>Flange : Without</p> <p>Mating Retention Type : Coupling Ring</p>
Dimensions	<p>Assembly Length (mm): 23</p> <p>Wire/Cable Size (AWG): 22</p>
Usage Conditions	<p>Operating Temperature Range (°C): -55 – 175</p> <p>IP Water Sealing Level : 7</p> <p>IP Dust Sealing Level : 6</p> <p>Fluid Resistance : Immersible</p>
Operation/Application	<p>Durability Rating (Cycles): 500</p>
Other	<p>Field Serviceable : Yes</p>
Statement of Compliance	<p>Statement of Compliance pdf</p>

Also in the Series | [AS Standard](#)

A photograph showing a yellow braided shielded cable with a circular connector and a separate black circular connector housing with multiple pins.

Standard Circular
Connectors (567)

Customers Also Bought

A collection of various black circular connectors and components.

TE Part # AS107-35PN-913F

RECEPT. IN LINE
TYPE 1 AS MICRO 7
CAD PL

A collection of various black circular connectors and components.

TE Part # ASU003-03SN-HE-913F

RECEPT ASSY 2 HOLE
MTG AS 3 WAY CAD
PLAT

A collection of various black circular connectors and components.

TE Part # AS607-35PA-913F

PLUG. BOOT
TERMIN. TYPE 6 AS
SIZE 7. CAD

A technical line drawing of a rectangular connector with a central pin and a side port.

TE Part # 342A124-12-0

342A124-12-0